

LogiLink HD0042 video switch HDMI

Gamintojas: **LOGILINK** · Modelis: **HD0042** · EAN: **4052792062403** · Prekės kodas: **674273**



34,90 €

Kaina su PVM

Be PVM: **28,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Allows multi-functional switching between three HDMI signal sources on one screen
- ✓ Compliant to HDMI 1.3 with a bandwidth of 2.5 Gbit/s 250 MHz per channel (7.5 Gbit/s total)
- ✓ Supports Full HD 1080p/60 Hz and Full 3D
- ✓ Supports HDCP Pass-Through
- ✓ Supports DDC and CEC function
- ✓ Support uncompressed audio such as LPCM7.1
- ✓ ABS chassis
- ✓ With remote control and IR receiver



Aprašymas

The LogiLink Full HD HDMI switch allows convenient switching between three HDMI input sources (video camera, DVD/Blu-ray player, game console, streaming box, etc.) via remote control, intelligent automatic detection or alternatively via switch on the switch itself. Annoying plugging and unplugging of cables is a thing of the past. Thanks to Full HD (1080p/60 Hz), you can experience media content in sharp resolution with support for HDCP (pass-through), CEC and 3D. The audio transmission in LPCM 7.1, DTS, Dolby Digital, DTS-HD Master Audio and Dolby TrueHD also leaves nothing to be desired.

Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Network > Switches [+2183][-1086]

Ports & interfaces

Video port type	HDMI
HDMI ports quantity	4
HDMI version	1.3
HDMI in	3
Number of HDMI outputs	1
3.5 mm (1/8-inch) in	Yes
DC-in jack	Yes

Features

Material	ABS
Product colour	Black
HDCP	Yes
Maximum refresh rate	60 Hz
Supported video modes	1080p
3D	Yes
Colour depth	36 bit
Dolby technologies	DTS, DTS-HD Master Audio, Dolby Digital, Dolby TrueHD
HDCP version	1.3

Power

Power consumption (max)	5 W
-------------------------	-----

Weight & dimensions

Width	58 mm
Depth	80 mm
Height	18 mm
Weight	54 g

Packaging content

Remote control included	Yes
Manual	Yes
Cables included	IR sensor

Operational conditions

Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-10 - 80 °C

Operating relative humidity (H-H)	10 - 85%
-----------------------------------	----------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------