

ATEN CL1308N-ATA-AU rack console 48.3 cm (19") Black 1U

Gamintojas: **ATEN** · Modelis: **CL1308N-ATA-AG** · EAN: **4719264642401** · Prekės kodas: **674582**



985,90 €

Kaina su PVM

Be PVM: **814,79 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- ✓ Integrated KVM console with 19" LED-backlit LCD panel
- ✓ A single console controls up to 128 computers by cascade to 2 levels and connect up to 8 switches
- ✓ USB or PS/2 keyboard and mouse emulation – computers boot even when the console focus is elsewhere



Aprašymas

With limited server room space and rising maintenance costs, network administrators are now more than ever looking for solutions that reduce both costs and space requirements. ATEN LCD KVM Switches offer a space saving, streamlined approach to KVM switching technology by integrating an LCD panel, full keyboard, and touchpad into a 1U rack-mountable sliding housing.

The CL1308 LCD KVM Switch features an integrated 19" LED-backlit LCD panel allowing access and control with up to 8 computers from a single console (keyboard, mouse, and monitor). As many as 8 additional switches can be cascaded bringing the total number of connected computers to 128 computers that can be controlled from a single keyboard-monitor-mouse console.

Setup is fast and easy; plugging cables into their appropriate ports is all that is needed. The switch supports both USB and PS/2 connections for the computers. The CL1308 intercepts keyboard input directly, thus eliminating the need for any software configuration. Switching between computers can be easily accomplished either by manually pressing the front panel push button port LEDs, entering hotkey combinations from the keyboard, or via a menu driven multilingual on-screen display (OSD) system.

Note: Optional rack mount kits are available. For more information, refer to Compatible Accessories below.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Display	
Display diagonal	48.3 cm (19")
Display	LCD
On Screen Display (OSD)	Yes
Technical details	
Rack capacity	1U
Product colour	Black
Hot-Plug support	Yes
Operating relative humidity (H-H)	0 - 80%
Maximum resolution	1920 x 1200 pixels
Rack mounting	Yes
Number of computers controlled	128
LED indicators	Yes
Push button	Yes
Compliance certificates	RoHS
Ports & interfaces	
VGA (D-Sub) ports quantity	8
Keyboard port type	PS/2
Mouse port type	USB
Video port type	VGA
Keyboard	
Keyboard language	US English
Keyboard layout	QWERTY
Hot keys	Yes
Power	
Power consumption (typical)	22 W
Input current	1 A
Operational conditions	
Operating temperature (T-T)	0 - 50 °C

Storage temperature (T-T)	-20 - 60 °C
---------------------------	-------------

System requirements

Windows operating systems supported	Yes
-------------------------------------	-----

Mac operating systems supported	Yes
---------------------------------	-----

Linux operating systems supported	Yes
-----------------------------------	-----

Weight & dimensions

Width	483 mm
-------	--------

Height	44 mm
--------	-------

Depth	689.2 mm
-------	----------

Weight	12.7 kg
--------	---------

Packaging data

Package weight	16.1 kg
----------------	---------

Package width	668 mm
---------------	--------

Package depth	833 mm
---------------	--------

Package height	135 mm
----------------	--------

Packaging content

Cables included	AC, KVM
-----------------	---------

Quick installation guide	Yes
--------------------------	-----

Manual	Yes
--------	-----

Rack mount kit	Yes
----------------	-----