

LogiLink HD0049 matrix switcher AV matrix switcher 5 W

Gamintojas: **LOGILINK** · Modelis: **HD0049** · EAN: **4052792062472** · Prekės kodas: **674684**



135,90 €

Kaina su PVM

Be PVM: **112,31 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Allow any A/V source to be displayed on multiple displays at the same time
- ✓ The Matrix switching functionality gives you full control of the video source displayed on each monitor
- ✓ Compliant to HDMI 2.0 with a bandwidth of 6.0 Gbit/s at 600 MHz per channel (18 Gbit/s total) and HDCP 2.2
- ✓ Supports DDC, HDR10 and Downscaler function (only 4K to 1080p with a latency of < 1ms)
- ✓ Supports ARC
- ✓ Support uncompressed audio such as LPCM7.1
- ✓ Metal chassis



Aprašymas

The LogiLink 4K HDMI matrix switch combines the advantages of a simple HDMI switch and a HDMI splitter. It routes one or two HDMI video signals from four selectable input signals to one or two selectable HDMI displays each. Control the unit remotely for maximum flexibility for all connected systems. All inputs are suitable for HD video sources such as video camera, HD DVD, receiver, set-top boxes, game consoles, etc. Thanks to Ultra HD (4K/60 Hz) experience media content in brilliantly sharp resolution. The integrated downscaler function supports the display of 4K content on Full HD displays, in addition, both 4K and Full HD displays can be operated simultaneously with support for HDCP 2.2, HDR, CEC as well as 3D. The audio transmission in LPCM 7.1, DTS, Dolby Digital, DTS-HD Master Audio and Dolby TrueHD as well as the connection of an external AV receiver (ARC), also leaves nothing to be desired.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Features	
Product type	AV matrix switcher
Bandwidth	6 Gbit/s
Audio channels	7.1
HDCP	Yes
HDCP version	2.2
3D	Yes
Remote Input Control Over DDC (RICOD)	Yes
High Dynamic Range (HDR) supported	Yes
Design	
Housing colour	Black
Housing material	Metal
LED indicators	Yes
Remote control included	Yes
Ports & interfaces	
HDMI input ports quantity	4
HDMI output ports quantity	2
HDMI version	2
Digital audio optical out	2
Digital audio coaxial in	2
Audio (L/R) out	2
DC-in jack	Yes
Power	
Power consumption (max)	5 W
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-10 - 80 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	5 - 90%
Logistics data	
Harmonized System (HS) code	85299097

Weight & dimensions

Width	210 mm
Depth	66 mm
Height	26 mm
Weight	340 g

Packaging content

Manual	Yes
AC adapter included	Yes