

LevelOne Fixed Dome IP Network Camera, 2-Megapixel, 802.3af PoE, IR LEDs

Gamintojas: **LEVEL ONE** · Modelis: **FCS-3101** · EAN: **4015867186671** · Prekės kodas: **674835**



268,90 €

Kaina su PVM

Be PVM: **222,23 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor & outdoor IP security camera
- ✓ CMOS 25.4 / 2.7 mm (1 / 2.7") 2 MP 1920 x 1080 pixels
- ✓ Wired Ethernet LAN
- ✓ Night vision 10 m IR
- ✓ Dome Ceiling/Desktop
- ✓ Black, White
- ✓ 380 g



Aprašymas

The LevelOne FCS-3101 is a palm-size and stylish design quality yet cost-effective surveillance solution for the home and office. It is designed for easy and flexible installation. Equipped with a 2-Megapixel sensor and built-in IR cut filter/IR illuminator LEDs, the camera provides high resolution quality and sharp sensitivity – ideal for security applications both day and night.

The FCS-3101 is equipped with many advanced features such as Level1DNS™ Service, alarm and sensor, a micro SD/SDHC card slot and USB interface for local storage, built-in microphone communications. Moreover, Support unique features for auto tracking function of moving objects, the system can send an E-mail alert or send captured images via FTP upload to a designated storage server. The FCS-3101 is indisputably the top choice for reliable and high performance surveillance.

- 2-Megapixel (1920 x 1080) high-definition resolution
- Compression: H.264/MPEG-4/MJPEG
- Removable IR-cut filter for day and night surveillance
- Supports 2 video streams simultaneously
- Built-in infrared LEDs for night viewing up to 10m
- Built-in Micro SD/SDHC card slot for local storage
- Built-in microphone for audio monitoring
- Dual power support: 12VDC/PoE (IEEE 802.3af)
- Free 64-channel monitoring software included (supports iCamSecure App)

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][-46]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
PTZ control	Yes
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Certification	CE, FCC, Onvif
Design	
Mounting type	Ceiling/Desk
Product colour	Black, White
Form factor	Dome
LED indicators	Link, Power
Country of origin	Taiwan
Camera	
Minimum illumination	1 lx
White balance	Auto
Camera shutter type	Electronic
Camera shutter speed	1/30 - 1/1000000 s
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	

Zoom capability	Yes
Focus adjustment	2
Fixed focal length	4 mm
Night vision	
Night vision	Yes
Night vision distance	10 m
LED type	IR
Number of illumination LEDs	19
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Video formats supported	MPEG4
Video compression formats	H.264, M-JPEG, MPEG4
Supported graphics resolutions	320 x 240, 640 x 480 (VGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Supported video modes	240p, 480p, 720p, 1080p
Frame rate	30 fps
Noise reduction	Yes
Automatic gain control	Yes
Full HD	Yes
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
Flip & mirror	Yes
Time stamp overlay	Yes
Audio	
Audio system	1-way
Built-in microphone	Yes
Voice codecs	AMR
Network	
Ethernet LAN	Yes
Wi-Fi	No
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3u
Supported network protocols	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, NTP, PPPoE, DNS, DHCP, RTSP, Samba
Storage	
Built-in HDD	No

Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash), MicroSDHC
Maximum memory card size	64 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Interface	RJ-45
Security	
Password protection type	User
IP address filtering	Yes
HTTPS encryption	Yes
Motion sensor	Yes
Management features	
Reset button	Yes
Power	
Power source type	PoE
AC input voltage	24 V
Power consumption (typical)	6 W
DC output current	1.5 A
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
System requirements	
Windows operating systems supported	Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Weight & dimensions	
Width	63 mm
Depth	63 mm
Height	93 mm

Weight	380 g
Packaging data	
Package width	205 mm
Package depth	155 mm
Package height	90 mm
Package weight	700 g
Package type	Box
Sustainability	
Compliance certificates	RoHS
Packaging content	
Mounting kit	Yes
Screws included	Yes
Manual	Yes
AC adapter included	Yes
Quick installation guide	Yes
Logistics data	
Harmonized System (HS) code	85258900
Technical details	
Number of video streams	2