

CyberPower OL1500ERTXL2U uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1350 W 8 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OL1500ERTXL2U** · EAN: **4712364143601** · Prekės kodas: **674979**



1 215,90 €

Kaina su PVM

Be PVM: **1 004,88 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Critical/Non-critical Load Outlets
- ✓ Smart Battery Management (SBM)
- ✓ Extended Battery Module (EBM)
- ✓ EMI and RFI Filtration
- ✓ LCD Status Display
- ✓ PowerPanel Management Software
- ✓ ECO Mode
- ✓ Overload Protection



Aprašymas

The Online Series UPS is ideal for servers, networking equipment, workstations and other mission-critical applications which require Pure Sinewave power protection. Featuring Online Double Conversion design and Zero Transfer Time, it can provide consistent and seamless Pure Sinewave power to critical loads. With the add-on advantage of Extended Runtime (XL) battery packs, the UPS backup time can be extended to maximize workflow flexibility. An optional SNMP/HTTP Remote Management Capability enables remote management and control of the system through standard web browser. The included PowerPanel® Business Edition management software provides corporate servers and critical workstations comprehensive network power management including unattended-shutdown, event logging, reporting, and notifications.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][−96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1.5 kVA
Output power	1350 W
Waveform	Pure sine
Input operation voltage (min)	190 V
Input operation voltage (max)	300 V
Input frequency	40/70 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	7.5 A
Surge energy rating	1780 J
Response time	0 ms
Heat dissipation	512 BTU/h
Output power factor	0.9
Emergency Power Off (EPO)	Yes
Total Harmonic Distortion (THD) (linear load)	3%
Total Harmonic Distortion (THD) (non-linear load)	5%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Surge protection features	Fax, Modem, Network, Telephone
Power protection features	Overload, Short circuit
Audible alarm(s)	Yes
Audible alarm modes	Battery replacement
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB 2.0 ports quantity	1
Serial interface	Yes

Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Ethernet LAN (RJ-45) ports	2
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	3 min
Typical backup time at half load	11 min
Battery recharge time	5 h
Hot-swap battery	Yes
Cold start	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Rack capacity	2U
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 45 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	C-TICK, CE, RCM, RoHS
Packaging content	
Rack mount kit	Yes
Cables included	Serial, USB cable

Manual	Yes
Weight & dimensions	
Width	433 mm
Depth	430 mm
Height	88 mm
Weight	18 kg
Packaging data	
Bundled software	PowerPanel® Business Edition
Package width	575 mm
Package depth	550 mm
Package height	240 mm
Package weight	24.5 kg
Logistics data	
Harmonized System (HS) code	8504408590
Warranty period	3 year(s)
Country of origin	China
Other features	
Battery type	RBP0074
Compatible operating systems	Windows 7 / Vista / XP / 2000, Server 2008 / 2003, Linux
Overload protection	Yes
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	23,66kg