

FSP Champ Tower 3K uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 2700 W

Gamintojas: **FSP** · Modelis: **PPF24A1807** · EAN: **4711140487618** · Prekės kodas: **675193**



577,90 €

Kaina su PVM

Be PVM: **477,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ True double-conversion
- ✓ Microprocessor control optimizes reliability
- ✓ Input power factor correction
- ✓ Output power factor 0.9
- ✓ Wide input voltage (120 V – 300 V)
- ✓ Converter mode available
- ✓ ECO mode for energy saving
- ✓ Generator compatible
- ✓ Charger capacity expansion to 6A for long-run models
- ✓ Smart SNMP works well with either USB or RS-232 together



Aprašymas

FSP Champ is the high density version of double-conversion online UPS with an output power factor that reaches 0.9 and featured with ECO mode for energy saving.

FSP Champ is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller.

Champ also have USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Sine
Input operation voltage (min)	120 V
Input operation voltage (max)	300 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	47/63 Hz
Output voltage regulation	1%
Response time	0 ms
Power factor	0.99
Crest factor	3:1
Total Harmonic Distortion (THD) (linear load)	3%
Total Harmonic Distortion (THD) (non-linear load)	6%
Noise level	50 dB
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
Number of output IEC jumpers	4
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1
Battery	
Battery capacity	9 Ah

Battery voltage	12 V
Number of battery cells	6
Typical backup time at full load	3.5 min
Typical backup time at half load	9.8 min
Battery recharge time(90%)	4 h
Design	
Form factor	Tower
Product colour	Black
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%
Packaging content	
Batteries included	Yes
Cables included	Input power cable, USB cable
Manual	Yes
Weight & dimensions	
Width	190 mm
Depth	421 mm
Height	318 mm
Weight	27.6 kg
Packaging data	
Software CD	Yes
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Packaging content	UPS, Power cable, USB cable, Software on CD, User manual
Matmenys ir svoris	
Matmenys (I × P × A)	56,00cm × 33,00cm × 46,00cm
Svoris	28,12kg