

LevelOne PoE Repeater, Cascadable

Gamintojas: **LEVEL ONE** · Modelis: **POR-0200** · EAN: **4015867185575** · Prekės kodas: **675636**



218,90 €

Kaina su PVM

Be PVM: **180,91 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Network repeater 200 m
- ✓ 10/100Base-T(X)
- ✓ Mounting type: Wall Power over Ethernet (PoE)
- ✓ Black



Aprašymas

Extend the reach of your PoE-Plus devices

For system integrators looking for a professional solution to help extend their PoE (802.3af/at) network, POR-0200 is the perfect accessory to increase your network performance.

Normal cable runs only reach 100 meters, but with POR-0200 installers can extend the PoE network performance up to 200 meters. Furthermore, you can triple your range or even more by daisy-chaining* multiple PoE repeaters.

* Maximum distance depends on the required Wattage of the PD.

Simple yet durable, no software required

As a PoE-Plus Repeater, POR-0200 receives all power from the Power Sending Equipment (PSE), such as a PoE-Plus switch. This means that POR-0200 uses no external power supply, making it the most flexible option for system integrators looking for an easy, affordable solution to increase the distance to the attached devices on a network. POR-0200 has 3 RJ-45 ports for easy deployment, 1 "IN" port that accepts the power and data for the first 100 meters, and 2 "OUT" ports for 1 PoE (power + data) and 1 non-PoE (data only) installation, that boosts and extends the device an additional

100 meters. With a durable metal housing, POR-0200 fits into any tight deployments.

Applications

POR-0020 is a long-ranged solution for deploying PoE IP Camera and any Fast Ethernet PoE PD powered by 802.3at PSE.

- High Power Midspan PoE compliant to simplify deployment and installation
- Built-in 2 output ports for 1 PoE and 1 non-PoE devices
- Forwards Power over Ethernet to remote device
- Extends PoE connection for another 100 meters
- Multiple PoE repeaters can be deployed by daisy chain to extend range
- Simple Plug and Play installation, no additional power supply required

Techninė specifikacija

Specifications	
Sandėlio grupė	WLAN Repeater [+54][-2]
Performance	
Type	Network repeater
Maximum transfer distance	200 m
Network	
Cabling technology	10/100Base-T(X)
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
Ports & interfaces	
Ethernet LAN (RJ-45) ports	3
Power over Ethernet (PoE) ports quantity	2
Design	
Product colour	Black
Mounting type	Wall
LED indicators	PoE, Power
Country of origin	Taiwan
Certification	FCC Part 15, CE
Power	
Power consumption (max)	2.5 W
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) voltage range	44 - 57 V
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	0 - 70 °C

Operating relative humidity (H-H)	5 - 95%
-----------------------------------	---------

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Weight & dimensions

Width	130 mm
-------	--------

Depth	90 mm
-------	-------

Height	28 mm
--------	-------

Weight	400 g
--------	-------

Packaging content

Quick start guide	Yes
-------------------	-----

Packaging data

Package type	Box
--------------	-----

Package width	146 mm
---------------	--------

Package depth	222 mm
---------------	--------

Package height	78 mm
----------------	-------

Package weight	600 g
----------------	-------

Certificates

Compliance certificates	RoHS
-------------------------	------

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------