

LevelOne GEMINI Zoom Dome IP Network Camera, 2-Megapixel, H.265, 4.3X Optical Zoom, two-way audio, IR LEDs, 802.3af PoE, Vandalproof, Indoor/Outdoor

Gamintojas: **LEVEL ONE** · Modelis: **FCS-4203** · EAN: **4015867203415** · Prekės kodas: **675644**



242,90 €

Kaina su PVM

Be PVM: **200,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2-Megapixel (1920 x 1080) high-definition resolution
- ✓ Video compression: H.264, H.265, MJPEG
- ✓ Supports 4.3X optical zoom
- ✓ Built-in infrared LEDs for night viewing up to 30m
- ✓ Vandal-proof IK10-rated housing
- ✓ Power support: PoE (IEEE 802.3af)
- ✓ Built-in Micro SD/SDHC card slot for local storage



Aprašymas

The LevelOne FCS-4203 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-4203 offers 2-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][[-46]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Certification	CE/FCC
Design	
Mounting type	Ceiling/wall
Product colour	White
Form factor	Dome
LED indicators	Power
Protection features	Vandal proof
International Protection (IP) code	IP66
IK code	IK10
Country of origin	China
Camera	
Minimum illumination	0.014 lx
Field of view (FOV) angle	112°
Camera shutter speed	1/3 - 1/10000 s
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 3 mm (1 / 3")
Progressive scan	Yes
Lens system	
Number of lenses	1
Optical zoom	4.3x
Focal length range	2.8 - 12 mm
Focus adjustment	1.4
Night vision	
Night vision	Yes

Night vision distance	30 m
LED type	IR
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	2 MP
Video formats supported	AVI
Video compression formats	H.264, M-JPEG
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Frame rate	30 fps
Full HD	Yes
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
Privacy masking	Yes
Audio	
Audio system	2-way
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Audio formats supported	G.711, G.726
Voice codecs	MP2L2, G.711, G.722.1, G.726
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.3af
Supported network protocols	TCP/IP (IPv4), UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Cabling technology	10/100Base-T(X)
Number of users	16 user(s)
Quality of Service (QoS) support	Yes
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	SD, SDHC, SDXC
Maximum memory card size	128 GB
Ports & interfaces	

Ethernet LAN (RJ-45) ports	1
Terminal block port	Yes
DC-in jack	Yes
Interface	RJ-45
Security	
Password protection	Yes
IP address filtering	Yes
HTTPS encryption	Yes
Anti-flicker	Yes
Heartbeat	Yes
Mirror	Yes
Digital watermark	Yes
Management features	
Web browser	Yes
Reset button	Yes
Power	
Power source type	PoE
Power consumption (max)	5.5 W
DC output voltage	12
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Operating relative humidity (H-H)	0 - 95%
System requirements	
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Weight & dimensions	
Width	133.1 mm
Depth	153.4 mm
Height	153.4 mm
Weight	1.29 kg
Packaging data	
Package width	174 mm
Package depth	173 mm

Package height	244 mm
Package weight	1.82 kg
Package type	Box
Sustainability	
Compliance certificates	RoHS
Packaging content	
Number of cameras	1
Screws included	Yes
Resource CD	Yes
Other features	
Data transfer rate	16 Mbit/s
Browser supported	Internet Explorer 9
Logistics data	
Harmonized System (HS) code	85258900
Master (outer) case width	365 mm
Master (outer) case length	372 mm
Master (outer) case height	504 mm
Master (outer) case gross weight	14.6 kg
Products per master (outer) case	8 pc(s)