

LevelOne FCS-3095 security camera Spherical IP security camera Indoor & outdoor 4000 x 3000 pixels Ceiling/Wall/Desk

Gamintojas: **LEVEL ONE** · Modelis: **FCS-3095** · EAN: **4015867203859** · Prekės kodas: **675654**



970,90 €

Kaina su PVM

Be PVM: **802,40 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1/1.7" Progressive Scan CMOS
- ✓ Max. 4000 × 3000 @20fps
- ✓ Up to 18 live view display modes
- ✓ Digital WDR
- ✓ Up to 15m IR range
- ✓ Built-in microphone and speaker
- ✓ Panomorph lens RPL: B9VVT

Aprašymas

FCS-3095 is a fisheye network camera capable of providing a 360-degree panoramic image of its surveillance scene.

The progressive scan CMOS sensor provides high-resolution images of up to 4000 × 3000.

Up to 18 live view display modes, designed for 3 mount types, meet various user preference.

Three independently controlled IR lights offer a range of 15 m and provide good vision in low or even zero-light environment.

Techninė specifikacija

Specifications

Sandėlio grupė

Netzwerkkameras [+927][-46]

Performance

Type IP security camera

Placement supported Indoor & outdoor

Connectivity technology Wired

PTZ control	Yes
Picture overlay	128 x 128 pixels
Picture overlay	24 bit
People counting function	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes

Design

Mounting type	Ceiling/Wall/Desktop
Product colour	White
Form factor	Spherical
Housing material	Metal
International Protection (IP) code	IP67
IK code	IK10
Fog proof	Yes

Camera

Minimum illumination	0 lx
Lens viewing angle, horizontal	180°
Lens viewing angle, vertical	180°
Camera shutter speed	1 - 1/100000 s

Image sensor

Sensor type	CMOS
Optical sensor size	25.4 / 1.7 mm (1 / 1.7")
Progressive scan	Yes

Lens system

Number of lenses	1
Maximum aperture number	2.2
Fixed focal length	2 mm

Night vision

Night vision	Yes
Night vision distance	15 m
LED type	IR
Number of illumination LEDs	3
Infra-red wavelength	850 nm

Video

Maximum resolution	4000 x 3000 pixels
Total megapixels	12 MP
Video compression formats	H.264, H.264+, H.265, H.265+, M-JPEG
Supported graphics resolutions	640 x 480 (VGA), 720 x 720, 2560 x 2560, 3000 x 3000, 4000 x 3000
Frame rate	30 fps
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
Privacy masking	Yes
Bit rate	32 Kbps - 16 Mbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Region of Interest (ROI) encoding	Yes

Audio

Built-in speaker(s)	Yes
Built-in microphone	Yes
Voice codecs	G.711, G.722.1, G.726, MP2L2, PCM
Bit rate range	16 - 160 Kbit/s
Sample rates	8 - 16 kHz

Network

Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Networking standards	IEEE 802.3at
Supported network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
Number of users	32 user(s)
User access level	Administrator, Operator, User
Live view	Yes
Number of simultaneous live view channels	20 channels

Storage

Built-in HDD	No
--------------	----

Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Maximum memory card size	256 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Microphone in	Yes
Headphone outputs	1
Security	
Alarm input channels	1
Alarm output channels	1
Password protection	Yes
Video motion detection	Yes
Active tampering alarm	Yes
IP address filtering	Yes
Security algorithms	802.1x RADIUS
HTTPS encryption	Yes
Intelligent Video Surveillance (IVS) system features	Abandoned object, Abnormal sound detection, Crossing line, Heat map, Intrusion, Region entrance detection, Region exiting detection
Anti-flicker	Yes
Heartbeat	Yes
Mirror	Yes
Digital watermark	Yes
Digest authentication	Yes
Management features	
Reset button	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	12.5 W
Power consumption (Power over Ethernet (PoE))	15 W
DC output voltage	12
DC output current	1 A
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	167 mm
Depth	152.8 mm
Height	55 mm
Weight	1.4 kg

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Svoris	1,00kg
--------	--------