

LevelOne Gemini Zoom IP Camera, 8-Mp, H.265, 802.3Af, PoE, IR Leds, Indoor/Outdoor, Two-Way Audio

Gamintojas: **LEVEL ONE** · Modelis: **FCS-3098** · EAN: **4015867228647** · Prekės kodas: **675656**



535,90 €

Kaina su PVM

Be PVM: **442,89 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8-Megapixel high-definition resolution
- ✓ Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- ✓ Built-in Micro SDHC/SDXC card slot for local storage
- ✓ Built-in infrared LEDs for night viewing up to 40m
- ✓ Dual power support: 12V DC/PoE (IEEE 802.3af)
- ✓ Video compression: H.264, H.265, MJPEG
- ✓ Vandal-proof IK10-rated housing
- ✓ Weatherproof IP67-rated housing
- ✓ Supports 4.3X optical zoom

Aprašymas

The LevelOne FCS-3098 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP67 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3098 offers 8-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Techninė specifikacija

Specifications

Sandėlio grupė

Netzwerkkameras [+927][-46]

Performance

Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Infrared (IR) cut-off filter	Yes
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
LED indicators	Power
International Protection (IP) code	IP67
IK code	IK10
Weatherproof	Yes
Country of origin	China
Camera	
Lens viewing angle, horizontal	35 - 115°
Lens viewing angle, vertical	19 - 60°
Lens viewing angle, diagonal	38.5 - 146°
Camera shutter speed	1/3 - 1/100000 s
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.5 mm (1 / 2.5")
Progressive scan	Yes
Lens system	
Zoom capability	Yes
Optical zoom	4.3x
Focal length range	2.8 - 12 mm
Maximum aperture number	2
Night vision	
Night vision	Yes
Night vision distance	30 m
Video	
Maximum resolution	3840 x 2160 pixels
Total megapixels	8 MP
Video compression formats	H.264, H.265

Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2560 x 1440, 2944 x 1656, 3840 x 2160
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
Digital Wide Dynamic Range (DWDR)	Yes
Audio	
Audio system	2-way
Voice codecs	G.711a, G.711u, G.722.1, G.726, MP2L2
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Networking standards	IEEE 802.3af
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP,SMTP, SNMP, IGMP, 802.1X, QoS, IPv4, IPv6
Quality of Service (QoS) support	Yes
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSDHC, MicroSDXC
Maximum memory card size	128 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Terminal block port	Yes
Security	
Password protection	Yes
Video motion detection	Yes
Active tampering alarm	Yes
IP address filtering	Yes
Security algorithms	EAP-LEAP, EAP-MD5, EAP-TLS, HTTPS, TLS
Alert notification type	E-mail, Snapshot alert message, Text alert message
Intelligent Video Surveillance (IVS) system features	Abandoned object, Crossing line, Face detection, Intrusion, Missing object, Scene change
Digital watermark	Yes
Management features	
Web-based management	Yes
Power	

Power source type	DC, PoE
Power consumption (typical)	11.5 W
Power consumption (max)	12.9 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	0 - 95 °C
Weight & dimensions	
Width	133.1 mm
Depth	153.4 mm
Height	153.4 mm
Weight	1.29 kg
Packaging data	
Package width	174 mm
Package depth	173 mm
Package height	244 mm
Package weight	1.42 kg
Package type	Box
Packaging content	
Number of cameras	1
Screws included	Yes
Logistics data	
Master (outer) cases per pallet (air)	18 pc(s)
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet height (air)	152 cm
Harmonized System (HS) code	8525890000
Master (outer) case width	365 mm
Master (outer) case length	372 mm
Master (outer) case height	504 mm
Master (outer) case gross weight	15 kg
Products per master (outer) case	12 pc(s)
Sustainability	
Sustainability compliance	Yes