

# LevelOne FCS-4072 GEMINI PTZ IP Camera, 4-MP, 32x Zoom, H.265, IR 200M, Indoor/Outdoor

Gamintojas: **LEVEL ONE** · Modelis: **FCS-4072** · EAN: **4015867236765** · Prekės kodas: **675658**



## 1 285,90 €

Kaina su PVM

Be PVM: **1 062,73 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 4-Megapixel high-definition resolution
- ✓ Built-in infrared LEDs for night viewing up to 200m
- ✓ Built-in Micro SD/SDHC card slot for local storage
- ✓ Dual power support: 24V AC/PoE
- ✓ Video compression: H.265, H.264, MJPEG
- ✓ Weatherproof IP66-rated housing
- ✓ Supports 32X optical zoom
- ✓ PTZ 360°
- ✓ Auto Tracking via event



## Aprašymas

The LevelOne FCS-4072 is a PTZ IP surveillance camera designed for use outdoors, boasting 4-Megapixel resolution and a 32X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area, and 200 meter IR led for night view clear. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

## Techninė specifikacija

**Specifications**

|                |                              |
|----------------|------------------------------|
| Sandėlio grupė | Netzwerkkameras [+927][[-46] |
|----------------|------------------------------|

**Performance**

|                              |                    |
|------------------------------|--------------------|
| Type                         | IP security camera |
| Placement supported          | Indoor & outdoor   |
| Connectivity technology      | Wired              |
| Infrared (IR) cut-off filter | Yes                |

**Design**

|                                    |                |
|------------------------------------|----------------|
| Mounting type                      | Wall           |
| Product colour                     | White          |
| Form factor                        | Dome           |
| LED indicators                     | Activity, Link |
| International Protection (IP) code | IP66           |
| Weatherproof                       | Yes            |
| Country of origin                  | China          |

**Camera**

|                           |                 |
|---------------------------|-----------------|
| Minimum illumination      | 0 lx            |
| Field of view (FOV) angle | 360°            |
| Tilt speed                | 120 °/sec       |
| Tilt preset speed         | 200 °/sec       |
| Pan speed                 | 160 °/sec       |
| Pan preset speed          | 240 °/sec       |
| Camera shutter speed      | 1/1 - 1/30000 s |

**Image sensor**

|                     |                          |
|---------------------|--------------------------|
| Sensor type         | CMOS                     |
| Optical sensor size | 25.4 / 1.8 mm (1 / 1.8") |
| Progressive scan    | Yes                      |

**Lens system**

|                    |                |
|--------------------|----------------|
| Number of lenses   | 1              |
| Optical zoom       | 32x            |
| Digital zoom       | 16x            |
| Focal length range | 5.9 - 188.8 mm |

**Night vision**

|              |     |
|--------------|-----|
| Night vision | Yes |
|--------------|-----|

|                                                      |                                                                                                                                                                     |
|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Night vision distance                                | 200 m                                                                                                                                                               |
| LED type                                             | IR                                                                                                                                                                  |
| Video                                                |                                                                                                                                                                     |
| Maximum resolution                                   | 2560 x 1440 pixels                                                                                                                                                  |
| Total megapixels                                     | 4 MP                                                                                                                                                                |
| Video compression formats                            | H.264, H.264+, H.265, H.265+, M-JPEG                                                                                                                                |
| Supported graphics resolutions                       | 352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2560 x 1440                                               |
| Frame rate                                           | 25 fps                                                                                                                                                              |
| Privacy masking                                      | Yes                                                                                                                                                                 |
| Audio                                                |                                                                                                                                                                     |
| Audio system                                         | 2-way                                                                                                                                                               |
| Voice codecs                                         | AAC, G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2, PCM                                                                                                               |
| Network                                              |                                                                                                                                                                     |
| Ethernet LAN                                         | Yes                                                                                                                                                                 |
| Wi-Fi                                                | No                                                                                                                                                                  |
| Bluetooth                                            | No                                                                                                                                                                  |
| Supported network protocols                          | IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour                                |
| Storage                                              |                                                                                                                                                                     |
| Built-in HDD                                         | No                                                                                                                                                                  |
| Card reader integrated                               | Yes                                                                                                                                                                 |
| Compatible memory cards                              | MicroSD (TransFlash), MicroSDHC, MicroSDXC                                                                                                                          |
| Maximum memory card size                             | 256 GB                                                                                                                                                              |
| Ports & interfaces                                   |                                                                                                                                                                     |
| Ethernet LAN (RJ-45) ports                           | 1                                                                                                                                                                   |
| Security                                             |                                                                                                                                                                     |
| Intelligent Video Surveillance (IVS) system features | Abandoned object, Abnormal sound detection, Face detection, Intrusion, Line crossing detection, Missing object, Region entrance detection, Region exiting detection |
| Power                                                |                                                                                                                                                                     |
| Power source type                                    | AC, DC, PoE                                                                                                                                                         |
| Power consumption (max)                              | 42 W                                                                                                                                                                |
| DC output voltage                                    | 24                                                                                                                                                                  |
| Operational conditions                               |                                                                                                                                                                     |
| Operating temperature (T-T)                          | -30 - 65 °C                                                                                                                                                         |

|                                   |         |
|-----------------------------------|---------|
| Operating relative humidity (H-H) | 5 - 95% |
|-----------------------------------|---------|

#### Weight & dimensions

|        |          |
|--------|----------|
| Width  | 220 mm   |
| Depth  | 220 mm   |
| Height | 353.4 mm |
| Weight | 5 kg     |

#### Packaging data

|                |        |
|----------------|--------|
| Package width  | 270 mm |
| Package depth  | 270 mm |
| Package height | 480 mm |
| Package weight | 5.5 kg |
| Package type   | Box    |

#### Sustainability

|                         |                                                                                                                                    |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Compliance certificates | BIS, CE, Electromagnetic Compatibility (EMC), Federal Communications Commission (FCC), Low Voltage Directive (LVD), RoHS, UKCA, UL |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------|

#### Packaging content

|                     |     |
|---------------------|-----|
| Number of cameras   | 1   |
| Mounting kit        | Yes |
| Screws included     | Yes |
| Manual              | Yes |
| AC adapter included | Yes |

#### Logistics data

|                                  |            |
|----------------------------------|------------|
| Pallet gross length              | 80 cm      |
| Pallet gross width               | 120 cm     |
| Pallet gross height              | 156.9 cm   |
| Customs product code (TARIC)     | 8525890000 |
| Harmonized System (HS) code      | 852589     |
| Master (outer) case width        | 450 mm     |
| Master (outer) case length       | 280 mm     |
| Master (outer) case height       | 550 mm     |
| Master (outer) case gross weight | 12 kg      |
| Products per master (outer) case | 2 pc(s)    |

#### Matmenys ir svoris

|        |        |
|--------|--------|
| Svoris | 9,70kg |
|--------|--------|