TP-Link InSight S285 Dome IP security camera Outdoor 3840 x 2160 pixels Ceiling

Gamintojas: **TP-LINK** · Modelis: **INSIGHT S285(4MM)** · EAN: **8885020624618** · Prekės kodas: **675697**

334,90 €

Kaina su PVM

Be PVM: **276,78 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K (8MP) Ultra HD and 24h Full-Color
- ✓ People & Vehicle Analytics†
- ✓ Human & Vehicle Classification
- ✓ Smart Detection
- ✓ Smart Video Enhancement Technology
- ✓ Active Defense and Two-Way Audio
- ✓ IP67 Waterproof and IK10 Vandal-Proof
- ✓ H.265+ Compression Technology

Aprašymas

All The Colors, All The Time
8MP Full-Color Dome Network Camera

People & Vehicle Analytics
Search and filter to people or vehicle of interest based on many different attributes, making post-event search faster and easier.

Human & Vehicle Classification
Distinguish humans and vehicles from other objects and receive more accurate event notifications.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Smart Video Enhancement Technology
True WDR: By analyzing and blending different exposures, True WDR ensures both bright and dark areas remain properly exposed, delivering a well-balanced and natural-looking image even in environments with high-contrast lighting.△

Smart IR: Smart IR dynamically adjusts infrared lighting to prevent overexposure and glare, improve visibility at different distances, and ensure clearer footage.

3D DNR: 3D DNR is a noise reduction technology that analyzes image data across frames to selectively reduce noise while preserving important details.

White Balance: White Balance ensures that white appears neutral in an image, regardless of the lighting conditions.

Efficient H.265+ Compression Technology
H.265+ reduces the required bandwidth and storage space for videos while maintaining excellent image quality. It saves 57.5% and 15% more storage space compared to H.264 and H.265, respectively.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][-46]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Maximum operating distance	107 m
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Remote viewing	Yes
Dynamic range	120 dB
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
Housing material	Metal
Protection features	Waterproof
International Protection (IP) code	IP67
IK code	IK10
Weatherproof	Yes
Camera	

Minimum illumination	0 lx
Lens viewing angle, horizontal	88°
Lens viewing angle, vertical	46°
Lens viewing angle, diagonal	105.4°
Tilt angle range	0 - 75°
Camera shutter speed	1/3 to 1/10000
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	
Detect distance	107 m
Observe distance	44 m
Recognize distance	21 m
Fixed focus	Yes
Maximum aperture number	1.6
Identify distance	11 m
Fixed focal length	4 mm
Night vision	
Night vision	Yes
LED type	IR/White
Video	
Maximum resolution	3840 x 2160 pixels
Total megapixels	8 MP
Video compression formats	H.264, H.264+, H.265, H.265+
Supported graphics resolutions	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520, 3840 x 2160
Video recording	Yes
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	Main Stream: 256 Kbps to 8 Mbps, Sub-Stream: 64 Kbps to 512 Kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Audio	

Built-in speaker(s)	Yes
Audio system	2-way
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Audio formats supported	G.711 A-law
Sample rate	8 kHz
Built-in microphone	Yes
Number of microphones	1
Bit rate range	0 - 64 Kbit/s
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Networking standards	IEEE 802.3af, IEEE 802.3at
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Live view	Yes
Storage	
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Built-in siren	Yes
Password protection	Yes
Video motion detection	Yes
IP address filtering	Yes
HTTPS encryption	Yes
Detection distance	107 m
Alert notification type	Push notification
Intelligent Video Surveillance (IVS) system features	Abnormal sound detection, Crossing line, Human detection, Intrusion, Line crossing detection, Moving object, Region entrance detection, Region exiting detection, Scene change, Vehicle detection
Motion sensor	Yes
Mirror	Yes

Human and vehicle targets classification	Yes
Digest authentication	Yes
Management features	
Cloud-managed	Yes
Web-based management	Yes
Web browser	Yes
Reset button	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	11 W
Power consumption (Power over Ethernet (PoE))	12.3 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Width	122 mm
Depth	122 mm
Height	89 mm
Weight	620 g
Packaging content	
Number of cameras	1
Manual	Yes
Matmenys ir svoris	
Svoris	0,90kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903