

CyberPower PR1500ERTXL2UCN uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1500 W 10 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR1500ERTXL2UCN** · EAN: **4711027797977** · Prekės kodas: **676569**



1 222,90 €

Kaina su PVM

Be PVM: **1 010,66 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 1.5 kVA 1500 W
- ✓ Waveform: Pure sine
- ✓ 10 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA)
- ✓ Rackmount Black



Aprašymas

PR1500ERTXL2UCN

CyberPower PR1500ERTXL2UCN with rackmount design guarantees power backup protection for home theater systems, multimedia devices, IT equipment, computers, workstations, NAS/Storage devices, telecom devices, networking devices, and surveillance systems. The UPS adopts line-interactive topology with Automatic Voltage Regulation (AVR) function, and offers stabilized Pure Sine Wave output to ensure high power quality. The UPS's output power factor is 1, which means it is capable of connecting to more critical loads than conventional UPS. It also features Battery Management Technology to help batteries obtain optimal life span by balancing battery string voltage. The quick charging technology allows fast and safe battery charging. Its multi-functional matrix LCD supports intuitive operation and quick configuration. The LCD panel is also rotatable to meet installation requirements.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	1.5 kVA
Output power	1500 W
Waveform	Pure sine
Input operation voltage (min)	131 V
Input operation voltage (max)	302 V
Input frequency	50/60 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	2430 J
Response time	6 ms
Heat dissipation	96.7 BTU/h
Output power factor	1
Emergency Power Off (EPO)	Yes
EMI/RFI noise filtering	Yes
Noise level	55.5 dB
Surge protection	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C14 coupler
AC outlets quantity	10 AC outlet(s)
USB port	Yes
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
Battery	

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	6.5 min
Typical backup time at half load	19.3 min
Battery recharge time	3 h
Hot-swap battery	Yes
Replacement battery cartridge	RBP0129
Design	
Form factor	Rackmount
Product colour	Black
Rack capacity	2U
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	0 - 95 °C
Certificates	
Compliance certificates	RoHS, CE, Federal Communications Commission (FCC), cUL, UL, VCCI
Weight & dimensions	
Width	433 mm
Depth	500 mm
Height	86.5 mm
Weight	32 kg