CyberPower PR1500ERTXL2UC uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1500 W 10 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR1500ERTXL2UC** · EAN: **4711027798912** · Prekės kodas: **676570**

1 069,89 €

Kaina su PVM

Be PVM: **884,21 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Active PFC Compatible
- ✓ Toolless Battery Replacement
- ✓ High Output Power Factor
- ✓ Overload Protection
- ✓ Quick Charging Technology
- ✓ Extended Battery Module (EBM)
- ✓ EMI and RFI Filtration
- ✓ USB Connectivity Port
- ✓ Emergency Power Off (EPO) Port

Aprašymas

CyberPower PR1500ERTXL2UC with rackmount design guarantees power backup protection for home theater systems, multimedia devices, IT equipment, computers, workstations, NAS/Storage devices, telecom devices, networking devices, and surveillance systems. The UPS adopts line-interactive topology with Automatic Voltage Regulation (AVR) function, and offers stabilized Pure Sine Wave output to ensure high power quality.

The UPS’s output power factor is 1, which means it is capable of connecting to more critical loads than conventional UPS. It also features Battery Management Technology to help batteries obtain optimal life span by balancing battery string voltage. The quick charging technology allows fast and safe battery charging. Its multi-functional matrix LCD supports intuitive operation and quick configuration. The LCD panel is also rotatable to meet installation requirements.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	1.5 kVA
Output power	1500 W
Waveform	Pure sine
Input operation voltage (min)	148 V
Input operation voltage (max)	288 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	16 A
Surge energy rating	2430 J
Response time	6 ms
Heat dissipation	96.7 BTU/h
Number of input phases	1
Number of output phases	1
Output power factor	1
Power Factor Correction (PFC) type	Active
Emergency Power Off (EPO)	Yes
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Detachable power cord	Yes
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	10 AC outlet(s)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	2
RS-232 ports	2
Ethernet LAN (RJ-45) ports	2
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Typical backup time at full load	6.5 min
Typical backup time at half load	19.3 min
Battery recharge time	3 h
Hot-swap battery	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Rack capacity	2U
Extended battery module rack capacity	2U
Cable length	3.05 m
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RCM, RoHS, UL, VCCI
Packaging content	
Batteries included	Yes
Rack mount kit	Yes
Cables included	Serial
Manual	Yes
Weight & dimensions	
Width	433 mm
Depth	500 mm
Height	86.5 mm
Weight	32 kg
Packaging data	
Package width	560 mm
Package depth	620 mm
Package height	275 mm
Package weight	38.8 kg
Package type	Box
Logistics data	
Country of origin	China
Other features	
Battery type	RBP0128
Sustainability	
Sustainability compliance	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903