

Dahua Technology PoE DH-SF1008L Unmanaged Fast Ethernet (10/100) Power over Ethernet (PoE) Desktop Light grey

Gamintojas: **DAHUA TECHNOLOGY** · Modelis: **DAHUA-SWITCH-DH-SF1008L** · EAN: **6923172583536** · Prekės kodas: **676711**



18,90 €

Kaina su PVM

Be PVM: **15,62 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Basic switching RJ-45 Ethernet ports quantity: 8
- ✓ Cat5e, Cat6 10BASE-T
- ✓ MAC address table: 2000 entries Switching capacity: 1.6 Gbit/s
- ✓ Desktop
- ✓ DC/PoE Power over Ethernet (PoE)



Aprašymas

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a plastic and fanless design, the device provides a more cost-effective option for customers. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

Plug and Play

Hassle-free, it does not require any configuration. Simply use after it is powered on.

Optimized Performance

All ports can transmit streams at high speeds without delay.

Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][-46]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Fast Ethernet (copper) ports quantity	8
Uplink ports quantity	1
Network	
10G support	No
Copper ethernet cabling technology	10BASE-T
Cable types supported	Cat5e, Cat6
Flow control support	Yes
Ethernet LAN data rates	10,100 Mbit/s
Data transmission	
MAC address table	2000 entries
Switching capacity	1.6 Gbit/s
Forwarding rate	0.744 Mpps
Packet buffer memory	0.768 MB
Design	
Rack mounting	No
Form factor	Desktop
Product colour	Light grey
LED indicators	Yes
Performance	
Mean time between failures (MTBF)	952.5 h
Power	
Power source	DC/PoE

DC input voltage	5 V
Input current	1 A
Power consumption (typical)	0.1 W
Power consumption (max)	0.5 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	132.9 mm
Depth	62.4 mm
Height	24 mm
Weight	160 g
Packaging data	
Package width	138 mm
Package depth	90 mm
Package height	63.5 mm
Package weight	290 g
Matmenys ir svoris	
Matmenys (I × P × A)	14,00cm × 9,00cm × 7,00cm
Svoris	0,22kg