

Conceptronic 3-Port 67W GaN USB PD Charger with USB-C Charging Cable, USB-C x 2, USB-A x 1, QC 3.0, PPS

Gamintojas: CONCEPTRONIC · Modelis: ALTHEA17B · EAN: 4015867236512 · Prekės kodas: 676787



43,90 €

Kaina su PVM

Be PVM: 36,28 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **High-Power GaN Technology:** This charger utilizes advanced Gallium Nitride (GaN) technology, providing up to 67W of total power for faster and more efficient charging.
- ✓ **Versatile Port Selection:** Equipped with 3 ports including 2 USB-C ports (with PD 3.0) and 1 USB-A ports (with QC 3.0), allowing simultaneous charging for multiple devices with varying power requirements.
- ✓ **Wide Compatibility:** Supports a range of output options from 3.3V to 20.0V across its ports, ensuring compatibility with devices from smartphones to laptops.
- ✓ **Enhanced Safety Features:** Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- ✓ **Efficiency and Fast Charging Technology:** Incorporates USB Power Delivery (PD) 3.0 and Quick Charge (QC) 3.0 technologies for rapid charging, along with Programmable Power Supply (PPS) compliance to maximize charging efficiency and minimize heat generation.
- ✓ **Included USB Cable:** Comes with a 1.5m 3.0A USB-C to USB-C cable for convenience and versatility.



Aprašymas

This charger leverages advanced Gallium Nitride (GaN) technology to deliver up to 67W of total power, ensuring faster and more efficient charging for your devices. It features a versatile port selection with 3 ports: 2 USB-C ports equipped with Power Delivery (PD) 3.0 and 1 USB-A port with Quick Charge (QC) 3.0. This setup allows for simultaneous charging of multiple devices with varying power requirements. The charger supports a broad

range of output options from 3.3V to 20.0V, making it compatible with a wide array of devices, from smartphones to laptops. Enhanced safety is provided through built-in protections against overload, short-circuiting, and overheating, safeguarding both the charger and connected devices. Additionally, it incorporates USB Power Delivery (PD) 3.0 and Quick Charge (QC) 3.0 technologies for rapid charging, along with Programmable Power Supply (PPS) compliance to optimize charging efficiency and reduce heat generation. For added convenience, the charger comes with a 1.5m 3.0A USB-C to USB-C cable.

Techninė specifikacija

Specifications	
Sandėlio grupė	Tablets & Smartphones [+3621][-199] Smartphone Zubehör [+2000][-87]
Performance	
Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
USB Type-C ports quantity	2
Fast charging	Yes
Fast charging technology	Power Delivery 3.0, Quick Charge 3.0
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
Power protection features	Overheating, Overload, Short circuit
Design	
Product colour	Black
Cable length	1.5 m
Gallium nitride (GaN) transistors	Yes
Power	
Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Input current	1.5 A
Maximum power	67 W
Maximum output voltage	20 V
Minimum output voltage	3.3 V
Output current (5V)	3 A
Output current (9V)	3 A
Output current (12V)	3 A
Output current (15V)	3 A

Output current (20V)	3.35 A
----------------------	--------

Weight & dimensions

Width	54 mm
Depth	54 mm
Height	32 mm
Weight	128 g

Packaging data

Package width	125 mm
Package depth	36 mm
Package height	110 mm
Package weight	110 g
Package type	Box

Operational conditions

Operating temperature (T-T)	0 - 35 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Packaging content

Cables included	USB Type-C
Manual	Yes

Certificates

Compliance certificates	CE, RoHS
-------------------------	----------

Sustainability

Sustainability certificates	ErP
Sustainability compliance	Yes

Logistics data

Harmonized System (HS) code	8504408390
Pallet gross width	120 cm
Pallet gross length	80 cm
Pallet gross height	146 cm
Master (outer) case width	385 mm
Master (outer) case length	240 mm
Master (outer) case height	265 mm
Master (outer) case gross weight	8.7 kg

Products per master (outer) case	40 pc(s)
----------------------------------	----------

Country of origin	China
-------------------	-------