

LevelOne GEMINI Fixed Dome IP Network Camera, 4-Megapixel, H.265, 802.3af PoE, IR LEDs, Indoor/Outdoor

Gamintojas: **LEVEL ONE** · Modelis: **FCS-3403** · EAN: **4015867207703** · Prekės kodas: **676893**



288,90 €

Kaina su PVM

Be PVM: 238,76 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4-Megapixel high-definition resolution
- ✓ Video compression: H.264, H.265, MJPEG
- ✓ Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- ✓ Built-in Micro SD/SDHC/SDXC card slot for local storage
- ✓ Built-in infrared LEDs for night viewing up to 30m
- ✓ Weatherproof IP66-rated housing
- ✓ Free surveillance and CMS (Central Management System) software packages with 64-channel license



Aprašymas

The LevelOne FCS-3403 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 4-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-3403 Should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][[-46]
Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Infrared (IR) cut-off filter	Yes
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
Protection features	Dust resistant, Heat resistant, Rain proof, Snow resistant
International Protection (IP) code	IP67
IK code	IK10
Weatherproof	Yes
Country of origin	China
Camera	
Minimum illumination	0 lx
Lens viewing angle, horizontal	86°
Lens viewing angle, vertical	46°
Lens viewing angle, diagonal	102°
Camera shutter speed	1/3 - 1/100000 s
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	
Number of lenses	1
Focus adjustment	2
Fixed focal length	4 mm
Night vision	
Night vision	Yes
Night vision distance	30 m

LED type	IR
Video	
Maximum resolution	2680 x 1520 pixels
Total megapixels	4 MP
Video formats supported	H.264, H.265, M-JPEG
Supported graphics resolutions	320 x 240, 352 x 240, 640 x 480 (VGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440, 2688 x 1520
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Image stabilizer	Yes
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
Flip & mirror	Yes
Portrait mode	Yes
Privacy masking	Yes
Time stamp overlay	Yes
Text caption overlay	Yes
Back Light Compensation (BLC)	Yes
Audio	
Audio formats supported	G.711 A-law, G.711 μ -law, G.722.1, G.726, MP2L2, PCM
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Networking standards	IEEE 802.1af
Supported network protocols	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP
Number of users	32 user(s)
Quality of Service (QoS) support	Yes
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Maximum memory card size	128 GB

Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Password protection	Yes
Video motion detection	Yes
Active tampering alarm	Yes
IP address filtering	Yes
Motion sensor	Yes
Anti-flicker	Yes
Heartbeat	Yes
Mirror	Yes
Digital watermark	Yes
Management features	
Reset button	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	8.5 W
Power consumption (Power over Ethernet (PoE))	10 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Weight & dimensions	
Height	82 mm
Diameter	11.1 cm
Weight	500 g
Packaging data	
Package width	134 mm
Package depth	134 mm
Package height	108 mm
Package weight	530 g
Package type	Box
Sustainability	

Compliance certificates

RoHS

Packaging content

Number of cameras

1

Screws included

Yes

Resource CD

Yes

Other features

Browser supported

Internet Explorer 8 above,Safari 8.0

Logistics data

Harmonized System (HS) code

85258900

Pallet net height

150 cm

Pallet net length

80 cm

Pallet net width

120 cm

Master (outer) case width

345 mm

Master (outer) case length

590 mm

Master (outer) case height

568 mm

Master (outer) case gross weight

608 g

Products per master (outer) case

24 pc(s)

Technical details

Number of video streams

3