

TP-Link Passthrough Powerline 600 Starter Kit, 1 Port

Gamintojas: **TP-LINK** · Modelis: **TL-PA4010PKIT** · EAN: **6935364031848** · Prekės kodas: **677110**



57,90 €

Kaina su PVM

Be PVM: **47,85 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1 Port per unit, 100Mbps
- ✓ HomePlug AV standard compliant, providing data transmission over electrical wires for HD video streaming
- ✓ Integrated power socket making sure that no power outlet is going to waste
- ✓ Plug and play design and easy encryption on a push of pair button
- ✓ Power-Saving Mode automatically reduces power consumption by up to 85%



Aprašymas

What This Product Does

The TL-PA4010P KIT turns your existing powerline into a high speed network with no need for new wires or drilling. No configuration is required, simply plug your adapter into your power socket and you can establish networking infrastructure in a flash. In addition, its integrated power socket makes sure that no power outlet is going to waste.

Easy Ethernet Connections

With advanced HomePlug AV technology, the TL-PA4010P KIT can provide users with a stable high-speed data transmission over a household electric circuit for up to 300 meters. the TL-PA4010P KIT is a great choice for a whole home solution to connect all network compatible devices--from computers and game consoles to set-top boxes for IPTV to printers and NAS hard drives.

Mains Filter for Better Performance

With its Integrated Mains Filter, the TL-PA4010P KIT can optimize powerline communication performance by suppressing noise interference generated by surrounding electronic equipment that can affect network performance. That means that users won't experience a sudden speed drop when a larger power consuming device is plugged into the power socket.

Pair Button for Easy Network Security

You can set up a hassle-free Powerline network within minutes with TP-Link's powerline adapters, just plug in and play. Also, the adapters' "Pair" buttons can be utilized for securing or managing multiple powerline adapters in your home powerline network.

1. Plug one Internet connected adapter into a nearby power outlet.
2. Connect additional adapters to PCs/laptops/Internet TVs or other networked devices via an Ethernet cable - and you're done!

Extra Power Socket for Additional Devices

With its integrated power socket, the new TL-PA4010P KIT provides real convenience for your home network. The integrated power socket allows an additional device or power bar to be connected to the adapter as though it were a normal wall socket. This ensures that even with the TL-PA4010P KIT plugged in, no power outlet is going to waste.

Reduce Power Consumption by Up to 85%

The TL-PA4010P KIT, a new-generation of Powerline Adapter, with its practical product design and environment-conscious Power-Saving Mode, will automatically switch from its regular "Working Mode" to "Power-Saving Mode" that will reduce energy consumption by up to 85%.

Techninė specifikacija

Specifications	
Sandėlio grupė	Powerlan [+41][-0]
Performance	
Maximum data transfer rate	600 Mbit/s
Ethernet LAN	Yes
Wi-Fi	No
Networking standards	IEEE 802.3, IEEE 802.3u
Built-in power socket	Yes
Ethernet LAN interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Ethernet LAN (RJ-45) ports	1
PowerLine standard	HomePlug AV
Modulation	OFDM
Security algorithms	128-bit AES
Maximum operating distance	300 m
Encryption button	Yes
Plug and Play	Yes
Power	

Power consumption (typical)	4.6 W
-----------------------------	-------

Power consumption (standby)	0.72 W
-----------------------------	--------

Design

Product colour	White
----------------	-------

LED indicators	Yes
----------------	-----

Certification	FCC, CE
---------------	---------

System requirements

Windows operating systems supported	Yes
-------------------------------------	-----

Linux operating systems supported	Yes
-----------------------------------	-----

Mac compatibility	Yes
-------------------	-----

Mac operating systems supported	Yes
---------------------------------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Weight & dimensions

Width	95 mm
-------	-------

Depth	58 mm
-------	-------

Height	42 mm
--------	-------

Certificates

Compliance certificates	RoHS
-------------------------	------

Packaging data

Package width	190 mm
---------------	--------

Package depth	136 mm
---------------	--------

Package height	100 mm
----------------	--------

Package weight	540 g
----------------	-------

Packaging content

Quantity per pack	2 pc(s)
-------------------	---------

Quick installation guide	Yes
--------------------------	-----

Cables included	LAN (RJ-45)
-----------------	-------------

Logistics data

Harmonized System (HS) code	85171800
-----------------------------	----------

Matmenys ir svoris

Matmenys (l × P × A)	19,00cm × 14,00cm × 10,00cm
Svoris	0,58kg