

CyberPower CP1200EIPFCLCD uninterruptible power supply (UPS) Line-Interactive 1.2 kVA 720 W 6 AC outlet(s)

 Gamintojas: **CYBERPOWER** · Modelis: **CP1200EIPFCLCD** · EAN: **4711027798585** · Prekės kodas: **678206**


330,90 €

Kaina su PVM

 Be PVM: **273,47 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 1.2 kVA 720 W
- ✓ Waveform: Sine
- ✓ 6 AC outlet(s)
- ✓ Tower Black



Aprašymas

CyberPower CP1200EIPFCLCD Line-Interactive USV 1200VA/720W Reine Sinuswelle, AVR, LCD, USB (HID), DB9, RJ45 Lan Protection, Ausgang (2) Schuko (4) IEC, Expansion Port für opt. Netzwerkkommunikation. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 1,2 kVA, Ausgangsleistung: 720 W. Stecker: C14-Koppler, Anzahl der AC-Ausgänge: 6 AC-Ausgänge, Verkabelungstechnologie: 10/100/1000Base-T(X). Typische Backup-Zeit bei voller Belastung: 3,1 min, Typische Backup-Zeit bei halber Belastung: 11,4 min, Akkuladezeit: 8 h. Formfaktor: Tower, Produktfarbe: Schwarz, Kabellänge: 1,83 m. Zertifizierung: RoHS

Techninė specifikacija

Specifications

Sandėlio grupė

USV & Stromversorgung [+611][-96]

Features

UPS topology	Line-Interactive
Output power capacity	1.2 kVA
Output power	720 W
Waveform	Sine
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	10 A
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Auto-restart	Yes

Ports & interfaces

Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	2
Cabling technology	10/100/1000Base-T(X)

Battery

Number of batteries supported	1
Typical backup time at full load	3.1 min
Typical backup time at half load	11.4 min
Battery recharge time	8 h

Design

Form factor	Tower
Product colour	Black

Cable length	1.83 m
Cooling type	Passive
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Certification	RoHS
Weight & dimensions	
Width	100 mm
Depth	355 mm
Height	280 mm
Weight	10 kg
Packaging data	
Package width	195 mm
Package depth	466 mm
Package height	370 mm
Package weight	11.6 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Matmenys ir svoris	
Svoris	11,44kg