

CyberPower OL5KERTHD uninterruptible power supply (UPS) Double-conversion (Online) 5 kVA 5000 W 6 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OL5KERTHD** · EAN: **4712856275902** · Prekės kodas: **678207**



3 245,90 €

Kaina su PVM

Be PVM: **2 682,56 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ ECO Mode
- ✓ High Output Power Factor
- ✓ Quick Charging Technology
- ✓ Automatic LCD screen orientation
- ✓ Rotatable LCD panel
- ✓ Surge and Spike Protection
- ✓ Critical/Non-critical Load Outlets
- ✓ Generator Compatible
- ✓ Battery Management Technology



Aprašymas

CyberPower OL5KERTHD guarantees power backup protection for IT equipment, servers, workstations, NAS/Storage devices, telecom devices, networking devices, security/emergency systems, and surveillance systems. The UPS adopts double-conversion topology to provide high-quality power output in a compact design. This generator-compatible UPS features hot-swappable battery packs for maintenance without power interruption, and comes with additional ECO Mode to conserve power and save on energy costs.

The UPS can employ Extended Battery Modules (EBM) to prolong runtimes, and adopts patented Battery Management Technology to balance battery string voltage for optimal battery lifespan. This model also features tiltable color LCD panel that allows users to monitor key power and battery information at a glance. The PowerPanel® Power Management Software allows user to perform real-time monitoring and remote management of the

UPS.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	5 kVA
Output power	5000 W
Waveform	Pure sine
Input operation voltage (min)	200 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	24 A
Surge energy rating	2430 J
Response time	0 ms
Heat dissipation	1186 BTU/h
Efficiency (ECO mode)	97%
Input power factor	0.99
Output power factor	1
Power Factor Correction (PFC) type	Active
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Total Harmonic Distortion (THD) (linear load)	3%
Total Harmonic Distortion (THD) (non-linear load)	5%
EMI/RFI noise filtering	Yes
Noise level	66 dB
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm

Ports & interfaces

AC outlet types	C13 coupler, C19 coupler, Terminal
Power plug	Terminal
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Emergency Power Off (EPO) connector	Yes

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	6 Ah
Battery voltage	12 V
Number of batteries supported	1
Typical backup time at full load	2.3 min
Typical backup time at half load	6.4 min
Battery recharge time	4 h
Hot-swap battery	Yes

Design

Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Control type	Buttons
Display type	LCD
LED indicators	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-5 - 45 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 4500 m

Certificates	
Compliance certificates	CE, EAC, RCM, RoHS
Packaging content	
Cables included	Serial, USB cable
Manual	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Sustainability compliance	Yes
Weight & dimensions	
Width	433 mm
Depth	720 mm
Height	86.5 mm
Weight	42 kg
Packaging data	
Package width	600 mm
Package depth	1100 mm
Package height	335 mm
Package weight	52 kg
Logistics data	
Harmonized System (HS) code	8504408690
Country of origin	China
Other features	
Battery type	RBP0144