

CyberPower OL3KERTHDL uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 3000 W 6 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OL3KERTHDL** · EAN: **4711027797960** · Prekės kodas: **678208**



2 702,90 €

Kaina su PVM

Be PVM: **2 233,80 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Double-conversion (Online)
- ✓ 3 kVA 3000 W
- ✓ Waveform: Pure sine
- ✓ 6 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA) 144 V
- ✓ Rackmount/Tower Black, Silver



Aprašymas

CyberPower OL3KERTHDL. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 3 kVA, Ausgangsleistung: 3000 W. AC-Steckertypen: C13-Koppler, C19-Koppler, Stecker: C19-Koppler, Anzahl der AC-Ausgänge: 6 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Akku-/Batteriespannung: 144 V, Typische Backup-Zeit bei voller Belastung: 5,7 min. Formfaktor: Rackmount/Tower, Produktfarbe: Schwarz, Silber, Gehäusematerial: Metall. Konformitätsbescheinigungen: CE, EAC, RCM, RoHS

Techninė specifikacija

Specifications

Sandėlio grupė

USV & Stromversorgung [+611][-96]

Features

UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	3000 W
Waveform	Pure sine
Input operation voltage (min)	200 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output frequency regulation	10 Hz
Output voltage regulation	2%
Maximum current	16 A
Surge energy rating	2430 J
Response time	0 ms
Heat dissipation	709 BTU/h
Number of input phases	1
Number of output phases	1
Efficiency (ECO mode)	97%
Input power factor	0.99
Output power factor	1
Power Factor Correction (PFC) type	Active
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Total Harmonic Distortion (THD) (linear load)	3%
Total Harmonic Distortion (THD) (non-linear load)	5%
EMI/RFI noise filtering	Yes
Noise level	66 dB
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
Power source type	AC

Socket circuit breaker	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C19 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery voltage	144 V
Number of batteries supported	1
Typical backup time at full load	5.7 min
Typical backup time at half load	12 min
Battery recharge time	4 h
Hot-swap battery	Yes
Rechargeable battery	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black, Silver
Housing material	Metal
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-5 - 45 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m

Non-operating altitude	0 - 4500 m
Certificates	
Compliance certificates	CE, EAC, RCM, RoHS
Packaging content	
Cables included	Serial, USB cable
Manual	Yes
Quick installation guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Sustainability compliance	Yes
Weight & dimensions	
Width	433 mm
Depth	720 mm
Height	86.5 mm
Weight	42 kg
Packaging data	
Package width	600 mm
Package depth	1100 mm
Package height	215 mm
Package weight	52.1 kg
Logistics data	
Country of origin	China
Other features	
Battery type	RBP0144
Nominal input voltage	220-240 V
Overload protection	Yes