

CyberPower OLS4KERT4UA-IEC uninterruptible power supply (UPS) Double-conversion (Online) 4 kVA 3800 W 15 AC outlet(s)

Gamintojas: CYBERPOWER · Modelis: OLS4KERT4UA-IEC · EAN: 4711027791784 · Prekės kodas: 678209



1 951,90 €

Kaina su PVM

Be PVM: 1 613,14 €

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Double-conversion (Online)
- ✓ 4 kVA 3800 W
- ✓ Waveform: Pure sine
- ✓ 15 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA)
- ✓ Rackmount/Tower Black



Aprašymas

CyberPower OLS4KERT4UA-IEC. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 4 kVA, Ausgangsleistung: 3800 W. AC-Steckertypen: C13-Koppler, C19-Koppler, Terminal, Stecker: Terminal, Anzahl der AC-Ausgänge: 15 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Typische Backup-Zeit bei voller Belastung: 6 min, Typische Backup-Zeit bei halber Belastung: 15 min. Formfaktor: Rackmount/Tower, Produktfarbe: Schwarz, Gehäusematerial: Metall. Konformitätsbescheinigungen: CE, RoHS

Techninė specifikacija

Specifications

Sandėlio grupė

USV & Stromversorgung [+611][-96]

Features

UPS topology	Double-conversion (Online)
Output power capacity	4 kVA
Output power	3800 W
Waveform	Pure sine
Input operation voltage (min)	110 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	200 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Output frequency regulation	0.5 Hz
Output voltage regulation	1%
Maximum current	20 A
Surge energy rating	1335 J
Heat dissipation	1777 BTU/h
Number of input phases	1
Number of output phases	1
Efficiency (ECO mode)	98%
Input power factor	0.99
Output power factor	0.95
Power Factor Correction (PFC) type	Active
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Total Harmonic Distortion (THD) (linear load)	1.5%
Total Harmonic Distortion (THD) (non-linear load)	2%
EMI/RFI noise filtering	Yes
Power source type	AC
Detachable power cord	Yes
Socket circuit breaker	Yes

Ports & interfaces

AC outlet types	C13 coupler, C19 coupler, Terminal
Power plug	Terminal
AC outlets quantity	15 AC outlet(s)

USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	3
RS-232 ports	3
Emergency Power Off (EPO) connector	Yes
SmartSlot	Yes

Battery

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	6 min
Typical backup time at half load	15 min
Battery recharge time	4 h
Charging current	4 A
Hot-swap battery	Yes

Design

Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Rack capacity	4U
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	CE, RoHS
Weight & dimensions	
Width	433 mm
Depth	661 mm
Height	171 mm
Weight	55 kg
Packaging data	
Package width	575 mm
Package depth	890 mm
Package height	404 mm
Package weight	73 kg
Package type	Box
Logistics data	
Country of origin	China
Other features	
Nominal input voltage	230 V
Overload protection	Yes
Quantity of delay expansion units (max)	4
Sustainability	
Sustainability compliance	Yes