

# CyberPower OL2200ERTXL2U uninterruptible power supply (UPS) Double-conversion (Online) 2.2 kVA 2000 W 9 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OL2200ERTXL2U** · EAN: **4711027799599** · Prekės kodas: **678210**



## 1 551,90 €

Kaina su PVM

Be PVM: **1 282,56 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Critical/Non-critical Load Outlets
- ✓ Smart Battery Management (SBM)
- ✓ Extended Battery Module (EBM)
- ✓ EMI and RFI Filtration
- ✓ LCD Status Display
- ✓ Emergency Power Off (EPO) Port
- ✓ SNMP/HTTP Remote Management Capability (Optional)
- ✓ ECO Mode



## Aprašymas

CyberPower OL2200ERTXL2U guarantees power backup protection for IT equipment, servers, workstations, NAS/Storage devices, telecom devices, networking devices, security/emergency systems, and surveillance systems. The UPS adopts double-conversion topology to provide high-quality power output with additional ECO Mode to conserve power and save on energy costs. This generator-compatible UPS features hot-swappable battery packs for maintenance without power interruption, and Emergency Power Off (EPO) switch to allow users to shut off UPS immediately during emergency.

To extend battery lifetime, the UPS adopts Smart Battery Management (SBM) to enhance battery charging process and achieve a lower total cost of ownership. This model also features detachable LCD display panel to relocate the panel for convenient monitoring, and RJ11/RJ45 port to provide

data line protection against surges and spikes. The PowerPanel Power Management Software allows user to perform real-time monitoring and remote management of the UPS.

## Techninė specifikacija

| Specifications                                    |                                   |
|---------------------------------------------------|-----------------------------------|
| Sandėlio grupė                                    | USV & Stromversorgung [+611][-96] |
| Features                                          |                                   |
| UPS topology                                      | Double-conversion (Online)        |
| Output power capacity                             | 2.2 kVA                           |
| Output power                                      | 2000 W                            |
| Waveform                                          | Pure sine                         |
| Input operation voltage (min)                     | 190 V                             |
| Input operation voltage (max)                     | 300 V                             |
| Input frequency                                   | 40/70 Hz                          |
| Output operation voltage (min)                    | 200 V                             |
| Output operation voltage (max)                    | 240 V                             |
| Output frequency                                  | 50/60 Hz                          |
| Maximum current                                   | 11 A                              |
| Surge energy rating                               | 1335 J                            |
| Response time                                     | 0 ms                              |
| Heat dissipation                                  | 1139 BTU/h                        |
| Output power factor                               | 0.9                               |
| Emergency Power Off (EPO)                         | Yes                               |
| Total Harmonic Distortion (THD) (linear load)     | 3%                                |
| Total Harmonic Distortion (THD) (non-linear load) | 5%                                |
| Surge protection                                  | Yes                               |
| Surge protection features                         | Fax, Modem, Network, Telephone    |
| Power protection features                         | Overload                          |
| Ports & interfaces                                |                                   |
| AC outlet types                                   | C13 coupler, C19 coupler          |
| Power plug                                        | C20 coupler                       |
| AC outlets quantity                               | 9 AC outlet(s)                    |
| USB 2.0 ports quantity                            | 1                                 |
| Serial interface                                  | Yes                               |
| Serial interface type                             | RS-232                            |

|                                     |     |
|-------------------------------------|-----|
| Serial ports quantity               | 1   |
| RS-232 ports                        | 1   |
| Ethernet LAN (RJ-45) ports          | 2   |
| Emergency Power Off (EPO) connector | Yes |

#### Battery

|                                  |                         |
|----------------------------------|-------------------------|
| Battery technology               | Sealed Lead Acid (VRLA) |
| Battery voltage                  | 72 V                    |
| Typical backup time at full load | 6.5 min                 |
| Typical backup time at half load | 20 min                  |
| Battery recharge time            | 5 h                     |
| Charging current                 | 1 A                     |
| Hot-swap battery                 | Yes                     |
| Cold start                       | Yes                     |

#### Design

|                  |                 |
|------------------|-----------------|
| Form factor      | Rackmount/Tower |
| Product colour   | Black           |
| Housing material | Metal           |
| Rack capacity    | 2U              |
| Cable length     | 3 m             |
| Cooling type     | Active          |
| Built-in fan     | Yes             |
| Control type     | Buttons         |
| Display type     | LCD             |
| LED indicators   | Yes             |

#### Operational conditions

|                                   |             |
|-----------------------------------|-------------|
| Operating temperature (T-T)       | 0 - 40 °C   |
| Storage temperature (T-T)         | -20 - 45 °C |
| Operating relative humidity (H-H) | 0 - 90%     |
| Storage relative humidity (H-H)   | 0 - 95%     |
| Operating altitude                | 0 - 3000 m  |
| Non-operating altitude            | 0 - 15000 m |

#### Certificates

|                         |          |
|-------------------------|----------|
| Compliance certificates | CE, RoHS |
|-------------------------|----------|

#### Packaging content

|                             |                   |
|-----------------------------|-------------------|
| Rack mount kit              | Yes               |
| Cables included             | Serial, USB cable |
| Manual                      | Yes               |
| Weight & dimensions         |                   |
| Width                       | 433 mm            |
| Depth                       | 600 mm            |
| Height                      | 88 mm             |
| Weight                      | 31 kg             |
| Packaging data              |                   |
| Package width               | 565 mm            |
| Package depth               | 880 mm            |
| Package height              | 240 mm            |
| Package weight              | 39.5 kg           |
| Logistics data              |                   |
| Harmonized System (HS) code | 8504408590        |
| Country of origin           | China             |
| Other features              |                   |
| Battery type                | RBP0076           |
| Sustainability              |                   |
| Sustainability compliance   | Yes               |