

CyberPower CP700EIPFCRM1U uninterruptible power supply (UPS) Line-Interactive 0.7 kVA 420 W 6 AC outlet(s)

Gamintojas: CYBERPOWER · Modelis: CP700EIPFCRM1U · EAN: 4711027798226 · Prekės kodas: 678212



380,90 €

Kaina su PVM

Be PVM: 314,79 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 0.7 kVA 420 W
- ✓ Waveform: Pure sine
- ✓ 6 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA)
- ✓ Rackmount Black, Silver



Aprašymas

CyberPower CP700EIPFCRM1U. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 0,7 kVA, Ausgangsleistung: 420 W. AC-Steckertypen: C13-Koppler, Stecker: C14-Koppler, Anzahl der AC-Ausgänge: 6 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Typische Backup-Zeit bei voller Belastung: 2 min, Typische Backup-Zeit bei halber Belastung: 9,6 min. Formfaktor: Rackmount, Produktfarbe: Schwarz, Silber, Gehäusematerial: Metall. Konformitätsbescheinigungen: CE, RoHS

Techninė specifikacija

Specifications

Sandėlio grupė

USV & Stromversorgung [+611][-96]

Features

UPS topology	Line-Interactive
Output power capacity	0.7 kVA
Output power	420 W
Waveform	Pure sine
Input operation voltage (min)	165 V
Input operation voltage (max)	271 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Output frequency regulation	3 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	10 A
Surge energy rating	450 J
Response time	6 ms
Heat dissipation	17 BTU/h
Number of input phases	1
Number of output phases	1
Power factor	0.6
Power Factor Correction (PFC) type	Active
Surge protection	Yes
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Socket circuit breaker	Yes

Ports & interfaces

AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
Serial interface	Yes
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	2

Battery

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	2 min
Typical backup time at half load	9.6 min

Battery recharge time	8 h
Hot-swap battery	Yes
Rechargeable battery	Yes
Design	
Form factor	Rackmount
Product colour	Black, Silver
Housing material	Metal
Cable length	1.83 m
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Quick installation guide	Yes
Weight & dimensions	
Width	433 mm
Depth	229.7 mm
Height	44 mm
Weight	8.3 kg
Packaging data	
Package width	530 mm
Package depth	280 mm
Package height	155 mm
Package weight	9.02 kg
Other features	
Battery type	RBP0019
Nominal output voltage	230 V

Nominal input voltage	220-240 V
Overload protection	Yes
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	9,68kg