

CyberPower CP900EIPFCLCD uninterruptible power supply (UPS) Line-Interactive 0.9 kVA 540 W 6 AC outlet(s)

 Gamintojas: **CYBERPOWER** · Modelis: **CP900EIPFCLCD** · EAN: **4711027798059** · Prekės kodas: **678213**


257,90 €

Kaina su PVM

 Be PVM: **213,14 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 0.9 kVA 540 W
- ✓ Waveform: Pure sine
- ✓ 6 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA)
- ✓ Tower Black



Aprašymas

CyberPower CP900EIPFCLCD. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 0,9 kVA, Ausgangsleistung: 540 W. AC-Steckertypen: C13-Koppler, Typ F, Stecker: C14-Koppler, Anzahl der AC-Ausgänge: 6 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Typische Backup-Zeit bei voller Belastung: 1 min, Typische Backup-Zeit bei halber Belastung: 7 min. Formfaktor: Tower, Produktfarbe: Schwarz, Gehäusematerial: Kunststoff. Konformitätsbescheinigungen: CE, RoHS

Techninė specifikacija

Specifications

Sandėlio grupė

USV & Stromversorgung [+611][-96]

Features

UPS topology	Line-Interactive
Output power capacity	0.9 kVA
Output power	540 W
Waveform	Pure sine
Input operation voltage (min)	170 V
Input operation voltage (max)	270 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	10 A
Surge energy rating	405 J
Response time	4 ms
Heat dissipation	31 BTU/h
Number of input phases	1
Number of output phases	1
Power Factor Correction (PFC) type	Active
EMI/RFI noise filtering	Yes
Surge protection	Yes
Surge protection features	Network, Telephone
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Detachable power cord	Yes
Socket circuit breaker	Yes

Ports & interfaces

AC outlet types	C13 coupler, Type F
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Ethernet LAN (RJ-45) ports	2

Battery

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	1 min
Typical backup time at half load	7 min
Battery recharge time	8 h
Design	
Form factor	Tower
Product colour	Black
Housing material	Plastic
Cable length	1.83 m
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Batteries included	Yes
Quick installation guide	Yes
Weight & dimensions	
Width	100 mm
Depth	275 mm
Height	230 mm
Weight	6.67 kg
Packaging data	
Package width	195 mm
Package depth	365 mm
Package height	355 mm
Package weight	7.95 kg

Other features	
Nominal output voltage	230 V
Nominal input voltage	220-240 V
Overload protection	Yes
Sustainability	
Sustainability compliance	Yes