
Eaton Rack/Tower 5PX2200IRTNG2 Line-Interactive USB/8x IEC C13/2x IEC C19 - incl. Netzwerkkarte

Gamintojas: **EATON** · Modelis: **5PX2200IRTNG2** · EAN: **743172104847** · Prekės kodas: **678496**



2,004.90€

Kaina su PVM

Be PVM: **1,656.94€**

Out Of Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Output power 2200 W, capacity 2.2 kVA
- ✓ Line-interactive topology with pure sine waveform
- ✓ Rackmount/tower form factor, 2U rack capacity
- ✓ Network management card included
- ✓ LCD display, LED indicators and USB port
- ✓ Input voltage range 160 V to 294 V

Aprašymas

The EATON 5PX 2200i RT2U Netpack G2 is a line-interactive uninterruptible power supply in a black rackmount/tower form factor with a 2U rack capacity. It delivers 2200 W of output power with a capacity of 2.2 kVA and a pure sine waveform.

The unit accepts input voltages from 160 V to 294 V and an input frequency of 47/70 Hz. It has a depth of 603 mm and operates at temperatures from 0 to 40 °C with a noise level of 40 dB.

- Network management card included
- LCD display and LED indicators
- USB port
- C20 coupler power plug
- Certification: IEC/EN 62040-2, FCC B, CISPR22 B CB (TUV) / cTUVus / EAC / UKCA / Ukr / Cm

Techninė specifikacija

Features	
Output power	2200W
Output power capacity	2.2 kVA

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Input operation voltage (max)	294V
Input frequency	47/70 Hz
Input operation voltage (min)	160V
UPS topology	Line-Interactive
Waveform	Pure sine
Noise level	40 dB
Design	
Product colour	Black
Form factor	Rackmount/Tower
LED indicators	Yes
Display type	LCD
Rack capacity	2U
Weight & dimensions	
Depth	603 mm
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Certificates	
Certification	IEC/EN 62040-2, FCC B, CISPR22 B CB (TUV) / cTUVus / EAC / UKCA / Ukr / Cm
Logistics data	
Harmonized System (HS) code	85078000
Ports & interfaces	
USB port	Yes
Power plug	C20 coupler
Packaging content	
Management card included	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	78.00cm × 58.00cm × 24.00cm
Svoris	40.00kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.