

ASUS RS720-E11-RS24U Intel C741 Rack (2U) Black, Silver

Gamintojas: **ASUS** · Modelis: **90SF01Z1-M008V0** · EAN: **4711387382653** · Prekės kodas: **678761**



3 940,90 €

Kaina su PVM

Be PVM: **3 256,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **Powerful performance:** Powered by 4th Gen Intel Xeon Scalable processors designed for potent data infrastructure from the cloud, to the network, to the intelligent edge
- ✓ **Scale-up storage and expansion design:** Up to 24 all-flash NVMe drives on the front panel and four PCIe 5.0 slots for higher bandwidth and system upgrade
- ✓ **Flexible networking module design:** Optional two 10 Gbps or four 1 Gbps on-board LAN module, and OCP 3.0 module with PCIe 5.0 slot in rear panel for faster connectivity
- ✓ **Advanced air cooling solution:** Features enhanced volume air cooling (EVAC) heatsink for processors with higher TDP
- ✓ **Enhanced IT-infrastructure management:** ASUS ASMB11-iKVM remote control with ASPEED AST2600, ASUS Control Center IT management software and hardware-level Root-of-Trust solution
- ✓ **Ready for AI and HPC workloads:** Supports 1 dual-slot GPU, including Intel Data Center GPU Flex series and NVIDIA A100



Aprašymas

PCIe 5.0 Ready

Faster storage, graphics and networking capabilities

PCI Express® (PCIe®) 5.0 delivers 32GT/s bandwidth, which is twice the speed of PCIe 4.0, and offers lower power consumption, better land scalability and backwards compatibility. ASUS servers are PCIe 5.0 ready with scalability design to satisfy the increasing workloads for modern data center.

Techninė specifikacija

Specifications	
Sandėlio grupė	PC-Systeme [+1197][-113]
Processor	
Built-in processor	No
Motherboard chipset	Intel C741
Number of processors supported	1
Processor manufacturer	Intel
Processor family	Intel® Xeon® Scalable
Compatible processor series	Intel® Xeon®
Memory	
Number of DIMM slots	32
Supported memory types	DDR5-SDRAM
Storage	
Number of storage drives supported	48
Hot-swap HDD bays	Yes
Storage drive sizes supported	2.5,3.5,M.2
Supported storage drive interfaces	Serial ATA, Serial Attached SCSI (SAS)
Graphics	
On-board graphics card model	Aspeed AST2600
On-board graphics card memory	64 MB
Maximum graphics card memory	64 MB
Network	
Ethernet LAN	Yes
Ethernet interface type	10 Gigabit Ethernet, Gigabit Ethernet
Ethernet LAN data rates	1000,10000 Mbit/s
LAN controller	Intel X710-AT2, Intel® I350-AM2
Ports & interfaces	
USB 2.0 ports quantity	0
Ethernet LAN (RJ-45) ports	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
IPMI LAN (RJ-45) port	Yes
Expansion slots	

PCI Express slots version	5
PCI Express x8 slots	2
PCI Express x16 slots	3
Features	
Trusted Platform Module (TPM)	Yes
Trusted Platform Module (TPM) version	2
Design	
Chassis type	Rack (2U)
Product colour	Black, Silver
LED indicators	Yes
Cooling type	Active
Number of fans	4 fan(s)
Power	
Power supply	1600 W
Number of redundant power supplies supported	2
80 PLUS certification	80 PLUS Platinum
Weight & dimensions	
Width	840 mm
Depth	447 mm
Height	88 mm
Weight	36 kg