

CyberPower LCD Line-Interactive USV 650VA/360WLCD, AVR, USB, Outlets (3) Schuko

Gamintojas: **CYBERPOWER** · Modelis: **BU650EULCD** · EAN: **4711027791999** · Prekės kodas: **679064**



102,90 €

Kaina su PVM

Be PVM: **85,04 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Automatic Voltage Regulation (AVR)
- ✓ LED Status Indicator
- ✓ Surge and Spike Protection
- ✓ PowerPanel Management Software
- ✓ EMI and RFI Filtration
- ✓ Energy Saving Technology
- ✓ LCD Status Display
- ✓ Overload Protection
- ✓ USB Connectivity Port



Aprašymas

CyberPower BU650EULCD provides home and office users with a reliable battery backup and safeguards office PCs and other electronic devices from surges, spikes, brownouts and other power irregularities. The product adopts line-interactive topology with Automatic Voltage Regulation (AVR) function to offer stabilized AC power output.

The patented GreenPower UPS™ Bypass design helps UPS achieve ultra-low power consumption to reduce energy costs while lowering UPS operating temperature, which extends its battery lifespan. Configurable alarm allows users to switch the audible alarm on or off during battery mode to avoid unnecessary disturbances. Its desktop design allows users to place it easily on desks or other tight spaces.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Line-Interactive
Output power capacity	0.65 kVA
Output power	360 W
Waveform	Simulated sine
Input operation voltage (min)	167 V
Input operation voltage (max)	295 V
Input frequency	50/60 Hz
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Output voltage regulation	10%
Automatic Voltage Regulation (AVR)	Yes
Maximum current	2.83 A
Surge energy rating	150 J
Heat dissipation	44.3 BTU/h
EMI/RFI noise filtering	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm, Fault
Ports & interfaces	
AC outlet types	Type F
Power plug	Type F
AC outlets quantity	3 AC outlet(s)
USB port	Yes
USB port type	USB Type-B
Battery	
Battery replacement accessibility	Professional only
Battery technology	Sealed Lead Acid (VRLA)
Battery recharge time	8 h
Design	
Form factor	Desktop

Product colour	Black
Housing material	Plastic
Cable length	1.2 m
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Non-operating altitude	0 - 3000 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Cables included	USB cable
Manual	Yes
Quick installation guide	Yes
Weight & dimensions	
Width	158 mm
Depth	240 mm
Height	91.5 mm
Weight	4.2 kg
Packaging data	
Package width	118 mm
Package depth	281 mm
Package height	225 mm
Package weight	9.68 kg
Other features	
Bypass	GreenPower UPS
Matmenys ir svoris	
Svoris	4,37kg