

TP-Link InSight S385DPS Bullet IP security camera Outdoor 5456 x 1520 pixels Wall

Gamintojas: **TP-LINK** · Modelis: **InSight S385DPS** · EAN: **8885020627824** · Prekės kodas: **679162**



776,90 €

Kaina su PVM

Be PVM: **642,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K (8MP) Ultra-High Definition
- ✓ Dual-lens Stitched Panoramic Imaging
- ✓ Ultra-Low Light ColorPro Night Vision
- ✓ Red-Blue Warning Lights and Sound Alerts
- ✓ People & Vehicle Analytics†
- ✓ Human & Vehicle Classification
- ✓ Smart Detection
- ✓ Smart Video Enhancement Technology
- ✓ Audio and Alarm Interface Available
- ✓ IP67 Weatherproof and IK10 Vandal-Proof



Aprašymas

See the big picture, capture every detail. This 4K (8MP) dual-lens stitched panoramic camera combines ultra-low-light ColorPro night vision, advanced analytics, and active audio-visual deterrence to deliver broader coverage, clearer evidence, and smarter alerts for critical broader indoor and outdoor areas, like parking lots, public squares, and industrial perimeters.

Panoramic Coverage, Richer Details

Dual-lens stitched panoramic imaging seamlessly fuses two lenses to expand the field of view, reduce blind spots, and cut the number of install points—lowering deployment costs.

4K (8MP) resolution paired with smart video enhancement boosts clarity and readability in backlight and low-light scenes for more reliable evidence.

Color at Night for Stronger Evidence

Ultra-low light ColorPro night vision delivers vivid color imaging in dark environments, preserving key identifiers like faces, apparel, and vehicle colors.

Smarter Detection, Precise Alerts

People & Vehicle Analytics and Human & Vehicle Classification distinguish targets to reduce false alarms; smart detection supports behaviors like intrusion, loitering, and line crossing to focus on real threats.
Red-blue warning lights and sound alerts provide visible and audible deterrence for proactive prevention and faster on-site intervention.

Easy Integration, Efficient Bandwidth

Audio and alarm interface enables linkage with external microphones, speakers, and sirens for a local response loop.
H.265+ compression maintains image quality while significantly reducing bandwidth and storage costs.

Built Tough for the Outdoors

IP67 weatherproofing and IK10 vandal-proof resistance ensure long-term reliability in harsh environments with minimal maintenance.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzwerkkameras [+927][(-46]
Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Maximum operating distance	76 m
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Remote viewing	Yes
Dynamic range	120 dB
Design	
Mounting type	Wall
Product colour	White
Form factor	Bullet
Housing material	Metal
Protection features	Waterproof
International Protection (IP) code	IP67
IK code	IK10
Weatherproof	Yes
Camera	

Minimum illumination	0 lx
Lens viewing angle, horizontal	180°
Lens viewing angle, vertical	51°
Lens viewing angle, diagonal	180°
Tilt angle range	0 - 90°
Camera shutter speed	1/3 to 1/10000
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 1.79 mm (1 / 1.79")
Progressive scan	Yes
Panoramic camera	
Sensor type (panoramic camera)	CMOS
Lens system	
Detect distance	76 m
Observe distance	29 m
Recognize distance	14 m
Fixed focus	Yes
Fixed focal length	5 mm
Night vision	
Night vision	Yes
LED type	IR/White
Video	
Maximum resolution	5456 x 1520 pixels
Total megapixels	8 MP
Video compression formats	H.264, H.264+, H.265, H.265+
Video recording	Yes
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	Main Stream: 256 Kbps to 8 Mbps, Sub-Stream: 64 Kbps to 1024 Kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Audio	
Built-in speaker(s)	Yes

Audio system	2-way
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Audio formats supported	G.711 A-law
Sample rate	8 kHz
Built-in microphone	Yes
Number of microphones	1
Bit rate range	0 - 64 Kbit/s
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Networking standards	IEEE 802.3at
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
SIM card slot	Yes
SIM card type	MicroSIM
Live view	Yes
Storage	
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Security	
Built-in siren	Yes
Password protection	Yes
Video motion detection	Yes
IP address filtering	Yes
HTTPS encryption	Yes
Alert notification type	Push notification
Motion sensor	Yes
Mirror	Yes
Human and vehicle targets classification	Yes
Digest authentication	Yes

Management features

Cloud-managed	Yes
Web-based management	Yes
Web browser	Yes
Reset button	Yes

Power

Power source type	DC, PoE
Power consumption (max)	18 W
Power consumption (Power over Ethernet (PoE))	21 W
DC output voltage	12

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	116 mm
Height	90 mm
Length	266 mm
Weight	1.12 kg

Packaging content

Number of cameras	1
Mounting kit	Yes
Screws included	Yes
Drilling template included	Yes
Manual	Yes