

# Conceptronic ZEUS 2200VA 1320W UPS, IEC + schuko socket

Gamintojas: **CONCEPTRONIC** · Modelis: **ZEUS04EM** · EAN: **4015867205211** · Prekės kodas: **679614**



## 266,90 €

Kaina su PVM

Be PVM: 220,58 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Built-in AVR protects against voltage fluctuation
- ✓ DC Start
- ✓ Powerful microprocessor design
- ✓ Includes a USB port
- ✓ AC auto restart



## Aprašymas

The Conceptronic UPS provides long-lasting, reliable battery backup for the home or small office. The unit is simple to install and operate, offering an easy and safe way of protecting your systems from harmful power surges and failures. Stylish, compact design makes the UPS ideal for limited office and home working spaces.

## Techninė specifikacija

### Specifications

Sandėlio grupė

USV & Stromversorgung [+611][-96]

### Features

UPS topology

Line-Interactive

|                                    |                                                                 |
|------------------------------------|-----------------------------------------------------------------|
| Output power capacity              | 2.2 kVA                                                         |
| Output power                       | 1320 W                                                          |
| Input operation voltage (min)      | 220 V                                                           |
| Input operation voltage (max)      | 240 V                                                           |
| Output operation voltage (min)     | 220 V                                                           |
| Output operation voltage (max)     | 240 V                                                           |
| Automatic Voltage Regulation (AVR) | Yes                                                             |
| Power protection features          | Overload                                                        |
| Audible alarm(s)                   | Yes                                                             |
| Audible alarm modes                | Alarm when on battery, Fault, Low battery alarm, Overload alarm |
| Auto-restart                       | Yes                                                             |
| Ports & interfaces                 |                                                                 |
| AC outlet types                    | IEC Jumpers, Type F                                             |
| AC outlets quantity                | 5 AC outlet(s)                                                  |
| Number of type F outputs           | 2                                                               |
| USB port                           | Yes                                                             |
| USB 2.0 ports quantity             | 1                                                               |
| Battery                            |                                                                 |
| Battery voltage                    | 24 V                                                            |
| Battery recharge time(90%)         | 8 h                                                             |
| Design                             |                                                                 |
| Form factor                        | Compact                                                         |
| Product colour                     | Black                                                           |
| Cooling type                       | Active                                                          |
| Built-in fan                       | Yes                                                             |
| LED indicators                     | Yes                                                             |
| Operational conditions             |                                                                 |
| Operating temperature (T-T)        | 0 - 40 °C                                                       |
| Operating relative humidity (H-H)  | 0 - 90%                                                         |
| Packaging content                  |                                                                 |
| Cables included                    | USB cable                                                       |
| Quick installation guide           | Yes                                                             |
| Weight & dimensions                |                                                                 |
| Width                              | 148 mm                                                          |

|                                  |          |
|----------------------------------|----------|
| Depth                            | 298 mm   |
| Height                           | 178 mm   |
| Weight                           | 10 kg    |
| Packaging data                   |          |
| Package width                    | 193 mm   |
| Package depth                    | 247 mm   |
| Package height                   | 335 mm   |
| Package weight                   | 10.4 kg  |
| Package type                     | Box      |
| Logistics data                   |          |
| Harmonized System (HS) code      | 85078000 |
| Master (outer) case width        | 210 mm   |
| Master (outer) case length       | 274 mm   |
| Master (outer) case height       | 356 mm   |
| Master (outer) case gross weight | 10.8 kg  |
| Products per master (outer) case | 1 pc(s)  |
| Country of origin                | China    |
| Other features                   |          |
| Battery type                     | MS7-12B  |