

Conceptronic ZEUS51E1K 1000VA 1000W Online UPS, IEC

Gamintojas: **CONCEPTRONIC** · Modelis: **ZEUS51E1K** · EAN: **4015867235447** · Prekės kodas: **679628**



401,90 €

Kaina su PVM

Be PVM: **332,15 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Output power factor 1.0
- ✓ ECO mode for energy saving
- ✓ Generator compatible
- ✓ Provides HID compatible USB connection
- ✓ Emergency Power Off (EPO) port
- ✓ Easy battery replacement
- ✓ THDi≤5%
- ✓ Outlet programmable management



Aprašymas

The Conceptronic Online UPS is the ultimate solution for reliable battery backup in your home or office. With an output power factor of 1.0, this UPS ensures maximum efficiency and performance. The ECO mode feature helps save energy, making it an environmentally friendly choice. Designed for compatibility with generators, it provides continuous power even during extended outages.

The Conceptronic Online UPS includes a HID-compatible USB connection for seamless communication with your devices and an Emergency Power Off (EPO) port for added safety during emergencies. The easy battery replacement feature allows for convenient maintenance. Additionally, the outlet programmable management feature enables you to customize power distribution according to your needs.

Simple to install and operate, the Conceptronic Online UPS offers a dependable and efficient way to protect your systems from power surges and failures, ensuring the smooth operation of your critical equipment.

Techninė specifikacija

Specifications	
Sandėlio grupė	USV & Stromversorgung [+611][-96]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	1000 W
Waveform	Sine
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Maximum current	10 A
Output power factor	1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Input current Total Harmonic Distortion (THD)	5%
Power protection features	Short circuit
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1
Programmable sockets	Yes
Battery	
Battery capacity	9 Ah
Battery voltage	12 V
Battery recharge time	4 h

Battery capacity	108 Wh
Design	
Form factor	Desktop
Product colour	Black
Cooling type	Active
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Rack mount kit	Yes
Cables included	Input power cable, RS-232, USB cable
Quick installation guide	Yes
Weight & dimensions	
Width	438 mm
Depth	430 mm
Height	88 mm
Weight	10.6 kg
Packaging data	
Screws included	Yes
Logistics data	
Products per pallet	32 pc(s)
Pallet gross length	120 cm
Pallet gross width	110 cm
Pallet gross height	2.15 m
Harmonized System (HS) code	8504402000
Master (outer) case width	550 mm
Master (outer) case length	566 mm
Master (outer) case height	226 mm
Master (outer) case gross weight	12.8 kg
Products per master (outer) case	1 pc(s)
Country of origin	China