

Conceptronic ZEUS52E3K 3000VA 2700W Online Tower UPS, IEC

Gamintojas: **CONCEPTRONIC** · Modelis: **ZEUS52E3K** · EAN: **4015867237847** · Prekės kodas: **679648**



661,89 €

Kaina su PVM

Be PVM: **547,02 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Output Power Factor 0.9
- ✓ ECO Mode for Energy-Saving
- ✓ Generator Compatible
- ✓ HID USB Communication
- ✓ Emergency Power Off (EPO) Port
- ✓ THDi≤5%



Aprašymas

Introducing the Conceptronic Online Tower UPS, the ultimate power backup solution for your home or office. With an ECO Mode for energy-saving operation and compatibility with generators, this UPS ensures continuous power even during extended outages. Equipped with HID USB communication, you can seamlessly connect and communicate with your devices for enhanced control and monitoring. For added safety during emergencies, the UPS is equipped with an Emergency Power Off (EPO) port, allowing for quick shutdown in critical situations. With its sleek tower design, the Conceptronic Online Tower UPS fits seamlessly into any environment, providing reliable power backup when you need it most.

Techninė specifikacija

Specifications

Sandėlio grupė

USV & Stromversorgung [+611][-96]

Features

UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Sine
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Maximum current	16 A
Output power factor	0.9
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Input current Total Harmonic Distortion (THD)	5%
Power protection features	Short circuit
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm

Ports & interfaces

AC outlet types	C13 coupler, C19 coupler
Power plug	C19 coupler
AC outlets quantity	5 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1

Battery

Battery capacity	9 Ah
Battery voltage	12 V
Battery recharge time	4 h
Battery capacity	108 Wh

Design

Form factor	Tower
-------------	-------

Product colour	Black
Cooling type	Active
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Cables included	Input power cable, RS-232, USB cable
Quick installation guide	Yes
Weight & dimensions	
Width	196 mm
Depth	416 mm
Height	342 mm
Weight	21.3 kg
Logistics data	
Products per pallet	16 pc(s)
Pallet gross length	100 cm
Pallet gross width	120 cm
Pallet gross height	12.6 cm
Harmonized System (HS) code	8504402000
Master (outer) case width	295 mm
Master (outer) case length	519 mm
Master (outer) case height	458 mm
Master (outer) case gross weight	22.3 kg
Products per master (outer) case	1 pc(s)
Country of origin	China
Matmenys ir svoris	
Svoris	25,88kg