

LogiLink PA0282 mobile device charger Mobile phone, Tablet White AC Fast charging Indoor

 Gamintojas: **LOGILINK** · Modelis: **PA0282** · EAN: **4052792067545** · Prekės kodas: **680024**


29,90 €

Kaina su PVM

 Be PVM: **24,71 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Equipped with GaN technology, performance and charging speeds are extremely powerful
- ✓ Supports PPS (Programmable Power Supply) charging and adjusting the output power in real-time, depending on device's charging status, feeding it with maxim+G818rs with better heat dissipation
- ✓ Overcurrent, overvoltage, overheating and short-circuit protection
- ✓ Compatible with most devices such as smartphones, tablets and more



Aprašymas

USB power socket adapter, 2x USB-C port (PD), GaN-Technology, 40 W" from LogiLink

The built-in GaN technology takes performance and charging speed to a whole new level with high efficiency. What makes this technology so special is its compact size and extremely powerful design. The USB socket adapter from LogiLink makes charging your USB-C devices child's play. The PA0282 supports PPS (Programmable Power Supply) charging and adjusting the output power in real-time, depending on device's charging status, feeding it with maximum power.

Proper use of the PD function can only be guaranteed in combination with certified USB cables with E-Mark chipset.

Techninė specifikacija

Specifications	
Sandėlio grupė	Tablets & Smartphones [+3621][-199] Smartphone Zubehör [+2000][-87]
Performance	
Charger type	Indoor
Charger compatibility	Mobile phone, Tablet
Power source type	AC
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
USB Type-C ports quantity	1
Fast charging	Yes
USB Power Delivery (USB PD)	Yes
Power protection features	Over voltage, Overcharge, Overheating, Short circuit
Design	
Product colour	White
Gallium nitride (GaN) transistors	Yes
Power	
Input voltage	230 - 240 V
Input frequency	50/60 Hz
Maximum power	40 W
AC adapter output current	1 A
Output current (5V)	3 A
Output current (9V)	2.22 A
Output current (12V)	1.67 A
Weight & dimensions	
Width	359 mm
Depth	925 mm
Height	55 mm
Weight	105 g
Packaging data	
Package type	Box
Operational conditions	
Operating temperature (T-T)	-10 - 40 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	35 - 85%

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Certificates

Compliance certificates	CE
-------------------------	----

Matmenys ir svoris

Svoris	0,14kg
--------	--------