

LogiLink UA0383 laptop dock/port replicator Wired USB 3.2 Gen 1 (3.1 Gen 1) Type-C Silver

Gamintojas: **LOGILINK** · Modelis: **UA0383** · EAN: **4052792064711** · Prekės kodas: **680049**



64,90 €

Kaina su PVM

Be PVM: **53,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Input: USB-C (male), 1x USB-C PD (female)
- ✓ Output: 3x 3.0 USB-A (female), 1x HDMI-A (female), 1x 3.5 mm audio port (female), 1x VGA (female), 1x RJ45 Gigabit Ethernet port (female), 1x SD/microSD card reader
- ✓ Connects up to 10 devices to a laptop/tablet through a single USB-C cable (0.12 m)
- ✓ Supports USB Power Delivery (USB-PD 3.0) for charging/usage of external devices with up to 100 W
- ✓ Supports SST (Single-Stream Transmission) in Windows
- ✓ Supports UHD 4K at 30 Hz resolutions (3840x2160) over HDMI with HEC, CEC, ARC and HDCP
- ✓ Supports Full HD 1080p at 60 Hz resolutions (1900x1200) over VGA
- ✓ Supports simultaneous use of VGA/HDMI
- ✓ Fast data transfer speeds of up to 5 Gbit/s
- ✓ Supports headphones and headsets



Aprašymas

The ideal USB 3.2 docking station with all-in-one solution to connect your USB-C laptop to multiple devices. You can connect UHD 4K projector and monitor, SD cards, speakers, headsets and USB flash drives to your laptop. USB-PD with up to 100 W continuous charge and a Gigabit Ethernet port are also supported, so you always have a secure Internet connection.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Hubs [+728][-6]
Ports & interfaces	
Connectivity technology	Wired
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
HDMI ports quantity	1
Headphone outputs	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	100 W
VGA (D-Sub) ports quantity	1
Headphone connectivity	3.5 mm
HDCP	Yes
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Performance	
Product colour	Silver
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash), SD
Data transfer rate	5000 Gbit/s
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	60 Hz
Housing material	Aluminium
Power	
Power source type	USB
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	115 mm
Depth	62.2 mm
Height	16.5 mm
Weight	97.6 g

Packaging content

Manual	Yes
--------	-----

Logistics data

Harmonized System (HS) code	84733020
-----------------------------	----------