Switch UBIQUITI USW-Pro-24-PoE Type L3 Desktop/pedestal Rack 24x10Base-T 100Base-TX 1000Base-T 2xSFP+ PoE ports 24 PoE+ ports 16 400 Watts USW-PRO-24-POE

Gamintojas: **UBIQUITI** · Modelis: **USW-PRO-24-POE** · EAN: **817882027649** · Prekės kodas: **68121**







820,90 €

Kaina su PVM

Be PVM: **678,43 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Aprašymas

Second-Generation UniFi Switching

We’ve redesigned our UniFi Switches from the ground up.

Near Silent Cooling

Our new airflow design reduces the need for fan usage.

Powerful Hardware and Software

UniFi Switches offer a variety of features, including 10G SFP+ ports, PoE+ or PoE++ support, and Layer 3* switching capabilities.

Redundant Power System

UniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply Failure

In the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPower

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

One UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen Display
The 1.3" touchscreen display allows easy monitoring and quick troubleshooting.
Summary: Ubiquiti UniFi Pro 24-Port PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 16000 entries, Switching capacity: 88 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: https://switch.ui.com/gen2/ | Switch type: Managed | Switch layer: L2/L3 | Quality of Service (QoS) support: Yes | Web-based management: Yes | System event log: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 2 | Power connector: AC-in jack | Networking standards: IEEE 802.3af/IEEE 802.3at | 10G support: Yes | Port mirroring: Yes | Full duplex: Yes | Broadcast storm control: Yes | Flow control support: Yes | IPv4 routes: 64 | Link aggregation: Yes | Rate limiting: Yes | VLAN support: Yes | Number of VLANs: 1000 | Switching capacity: 88 | Throughput: 44000 | Forwarding rate: 65.472 | MAC address table: 16000 | Static route: Yes | Jumbo frames support: Yes | Packet buffer memory: 2 | DHCP features: DHCP relay/DHCP server/DHCP snooping | IGMP snooping: Yes | Authentication type: IEEE 802.1x,RADIUS | Rack mounting: Yes | Form factor: 1U | Product colour: Silver | Reset button: Yes | LED indicators: Activity/Link/PoE/Speed/System | Display type: LCM | Power source: AC | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Number of power supply units: 1 | AC input voltage: 100 - 240 | AC input frequency: 50 - 60 | Power consumption (max): 450 | Power over Ethernet (PoE): Yes | Power over Ethernet plus (PoE+) ports quantity: 16 | Power over Ethernet 4PPoE (PoE++) ports quantity: 8 | Power over Ethernet (PoE) power per port: 64 | Total Power over Ethernet (PoE) budget: 400 | Operating temperature (T-T): -5 - 40 | Operating relative humidity (H-H): 10 - 90 | Width: 442.4 | Depth: 285.4 | Height: 43.7 | Weight: 4300 | Certification: CE, FCC, IC | Harmonized System (HS) code: 85176990 | Unit Calculated Weight: 6.5 | Product Net Weight: 4.3 | Unit Calculated Volume: 0.03005 | Units per Shipping Box: 2 | Unit Width: 12.5 | Shipping Box Height: 42 | Unit Depth: 51 | Unit Height: 38 | Name: NET SWITCH 24PORT 1000M 2SFP/POE USW-PRO-24-POE UBIQUITI | Model name: USW-Pro-24-PoE

Techninė specifikacija

Konstrukcija	
Produkto spalva	Silver
Matmenys ir svoris	
Matmenys (I × P × A)	51,00cm × 13,00cm × 38,00cm