Wireless Router TELTONIKA Router 300 Mbps 4G RUTX12

Modelis: RUTX12

Gamintojas: TELTONIKA

EAN: 4779027312743

Prekės kodas: 68134

518.99€

Powerful Dual LTE Cat 6 router is designed for mission critical applications. Two simultaneously operational LTE CAT 6 modems can provide speeds up to 600 Mbps with load balancing feature. This makes this device irreplaceable in applications where loosing connection is not an option.

Two LTE modules working simultaneously can provide speeds up to 600 Mbps

Instant failover switching

5 x Gigabit Ethernet with speeds up to 1000 Mbps

Teltonika Remote Management System compatible

Easy to use, secure and feature rich OpenWrt based Operating System

Summary: Teltonika RUTX12. WAN connection type: RJ-45. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 867 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3au, IEEE 802.3az. Mobile network generation: 4G, 4G standard: LTE. Security algorithms: DES, IPSEC | Vendor Homepage: https://teltonika-networks.com/product/rutx12/ | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Wi-Fi standards: 802.11a/802.11b/802.11g/Wi-Fi 4 (802.11n)/Wi-Fi 5 (802.11ac) | WLAN data transfer rate (max): 867 | 3G/4G USB modem compatibility: Yes | Ethernet WAN: Yes | SIM card slot: Yes | WAN connection type: RJ-45 | Auto MDI/MDI-X: Yes | Dynamic DNS (DDNS): Yes | Ethernet LAN: Yes | Ethernet LAN data rates: 10/100/1000 | Ethernet LAN interface type: Gigabit Ethernet | Networking standards: IEEE 802.3/IEEE 802.3af/IEEE 802.3at/IEEE 802.3au/IEEE 802.3az | 3G: Yes | 4G: Yes | 4G standard: LTE | Dual SIM support: Yes | Mobile network generation: 4G | Short Message Service (SMS): Yes | Ethernet LAN (RJ-45) ports: 5 | USB port: Yes | Quality of Service (QoS) support: Yes | Reset button: Yes | Access Control List (ACL): Yes | Filtering: Yes | Firewall: Yes | Security algorithms: DES/IPSEC | DHCP client: Yes | Supported network protocols: TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL v3, TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet client, SNMP, MQTT, Wake on LAN (WOL) | Housing material: Aluminium | LED indicators: Power,Status | Product colour: Silver | Product type: Tabletop router | Certification: CE/RED, EAC, RoHS, WEEE Draft ETSI EN 301 489-1 V2.2.0, Draft EN 301 489-19 V2.1.0, Draft ETSI EN 301 489-52 V1.1.0 EN 61000-4-2:2009 EN 300 511 V12.5.1, ETSI EN 301 908-1 V11.1.1, ETSI EN 301 908-2 V11.1.2, ETSI EN 301 908-13 V11.1.2 EN 61000-4-3:2006 + | Manual: Yes | Quick start guide: Yes | Antenna design: Internal | Antennas quantity: 8 | Built-in processor: Yes | Flash memory: 256 | Internal memory: 256 | Processor architecture: ARM Cortex A7 | Processor cores: 4 | Processor frequency: 717 | Safety: IEC 62368-1:2014, EN 50385:2017, EN 62232:2017 | Power over Ethernet (PoE): Yes | Power source type: DC | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 95 | Height: 44 | Weight: 540 | Width: 132 | Harmonized System (HS) code: 85176990 | Model: RUTX12 | Model name: RUTX12000000 | Units per Pallet: 0 | Units per Shipping Box: 5 | Unit Calculated Volume: 0.004618 | Unit Calculated Weight: 1.17