



# Switch

## MIKROTIK Type

### L3 Rack

#### 24x10Base-T

#### 100Base-TX

#### 1000Base-T

#### 4xSFP+ 1xRJ45

#### CRS328-24P-

#### 4S+RM

Modelis: CRS328-24P-4S+RM

Gamintojas: MIKROTIK

EAN: 4752224002228

Prekės kodas: 68139

---

## 443.99€

---

CRS328-24P-4S+RM is a 28 independent port switch, it has 24 Gigabit Ethernet ports, which offer different power output options: Passive PoE, low voltage PoE, 802.3af/at (Type 1 "PoE" / Type 2 "PoE+") with auto-sensing. PoE-Out is passed over mode B pins (4,5+)(7,8-). The four SFP+ ports provide up to 10 Gbps connectivity options via either optical fiber or Ethernet modules (not included).

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

CRS328-24P-4S+RM comes in a 1U rackmount case with 100-240 V AC 500 W power supply built-in. The device consumes up to 44 W leaving guaranteed 450 W (3x150 W per every 8 Ethernet ports) to power your PoE devices. Each port can provide up to 30 W of power with any power output option you choose.

The device has a “Dual boot” feature that allows you to choose between two operating systems - RouterOS or SwOS. If you prefer to have a simplified operating system with only switch specific features, use SwOS. If you would like the ability to use routing and other Layer 3 features in your CRS, use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings. All the feature set comes with disruptive price, providing best price/performance on the market.

- CPU temperature monitor
- Current Monitor
- PCB temperature monitor
- Voltage Monitor
- Mode button

Summary: Mikrotik CRS328-24P-4S+RM. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24, Console port: RJ-45. MAC address table: 16000 entries, Switching capacity: 128 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.3ad. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: [https://mikrotik.com/product/crs328\\_24p\\_4s\\_rm](https://mikrotik.com/product/crs328_24p_4s_rm) | Quality of Service (QoS) support: Yes | Switch layer: L2/L3 | Switch type: Managed | System event log: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Console port: RJ-45 | SFP+ module slots quantity: 4 | Auto-sensing: Yes | Broadcast storm control: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1Q/IEEE 802.3ad | Number of VLANs: 4000 | Port mirroring: Yes | VLAN support: Yes | Forwarding rate: 95.2 | Jumbo frames: 10218 | Jumbo frames support: Yes | MAC address table: 16000 | Switching capacity: 128 | Throughput: 64000 | Access Control List (ACL): Yes | IGMP snooping: Yes | Management protocols: SNMP | Form factor: 1U | LED indicators: Yes | Number of fans: 2 | Product colour: White | Rack mounting: Yes | Built-in processor: Yes | Flash memory: 16 | Internal memory: 512 | Mean time between failures (MTBF): 200000 | Processor frequency: 800 | Processor manufacturer: ARM | AC input voltage: 100 - 240 | Number of power supply units: 2 | Power consumption (max): 44 | Power

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

source: AC | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 24 | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet (PoE) type supported: Passive PoE/PoE+ | Power over Ethernet (PoE) voltage: 26 | Total Power over Ethernet (PoE) budget: 450 | Operating temperature (T-T): -20 - 60 | Depth: 300 | Height: 44 | Width: 443 | Cables included: AC | Rack mount kit: Yes | Harmonized System (HS) code: 85176990 | Units per Pallet: 88 | Units per Shipping Box: 2 | Unit Calculated Volume: 0.03088 | Unit Calculated Weight: 5.28

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903