



Switch TP-LINK Omada TL- SG2428P Type L2+ 24x10Base- T 100Base-TX 1000Base-T 4xSFP PoE+ ports 24 250 Watts TL- SG2428P

Modelis: TL-SG2428P

Gamintojas: TP-LINK

EAN: 6935364030650

Prekės kodas: 68156

315.99€

TP-Link's brand new Omada smart switches provide huge upgrade comparing with previous versions. The switches can be managed by Omada SDN Controller, which provides professional and reliable one-step solutions. Integrated L2 and L2+ features such as 802.1Q VLAN, QoS, IGMP Snooping and

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

static routing provide cost-effective networking solutions for small and medium-sized businesses without sacrificing enhanced usability and strong performance.

- 24× Gigabit 802.3af/at PoE+ ports and 4× Gigabit SFP slots
- 250 W total PoE budget with up to 30 W PoE output per port*
- Centralized cloud management via the web or the Omada app†
- Standalone management via web, CLI, SNMP, and RMON
- Static Routing helps route internal traffic for higher efficiency
- VLAN, ACL, QoS, and IGMP Snooping
- Durable metal casing and rackmountable design

Summary: TP-Link Omada 28-Port Gigabit Smart Switch with 24-Port PoE+. Switch type: Managed, Switch layer: L2/L2+. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 8000 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE.... Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://www.tp-link.com/en/business-networking/omada-switch-poe/sg2428p/#overview> | ARP inspection: Yes | MIB support: Y | Quality of Service (QoS) support: Yes | Switch layer: L2/L2+ | Switch type: Managed | System event log: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 24 | SFP module slots quantity: 4 | 10G support: No | Broadcast storm control: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e | Copper ethernet cabling technology: 1000BASE-T/10BASE-T | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1D/IEEE 802.1p/IEEE 802.1Q/IEEE 802.1s/IEEE 802.1w/IEEE 802.1x/IEEE 802.3ab/IEEE 802.3ad/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | Number of VLANs: 4000 | Port mirroring: Yes | Rate limiting: Yes | Spanning tree protocol: Yes | Virtual LAN features: MAC address-based VLAN/Protocol-based VLAN/Voice VLAN | VLAN support: Yes | Fiber ethernet cabling technology: 1000BASE-X | Forwarding rate: 41.66 | Jumbo frames: 9000 | Jumbo frames support: Yes | MAC address table: 8000 | Number of queues: 8 | Packet buffer memory: 4.1 | Switching capacity: 56 | Access Control List (ACL): Yes | Authentication type: RADIUS | BPDU filtering/protection: Yes | DHCP features: DHCP client/DHCP relay/DHCP server/DHCP snooping/DHCPv6 client | IGMP snooping: Yes | IP-MAC-Port binding: Yes | Queue scheduling algorithms: SP/Weighted Round Robin (WRR)/WRR+SP | Security algorithms: HTTPS/SNMP/SNMPv2/SNMPv3/SSH/SSH-2/SSL/TLS | SSH/SSL

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

support: Yes | Multicast support: Yes | Management protocols: SNMPv1/v2c/v3, SNTTP | Form factor: 1U | Number of fans: 2 | Product colour: Black | Rack mounting: Yes | Firmware upgradeable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 301.1 | Power source: AC | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet plus (PoE+) ports quantity: 24 | Total Power over Ethernet (PoE) budget: 250 | Heat dissipation: 1052.94 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 50 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 220 | Height: 44 | Width: 440 | Cables included: AC | Rack mount kit: Yes | User guide: Yes | Certification: CE, FCC, RoHS | Series: Omada | Model name: Omada 28-Port Gigabit Smart Switch with 24-Port PoE+ | Units per Shipping Box: 4 | Unit Calculated Volume: 0.02104 | Unit Calculated Weight: 4.22

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903