



Switch DAHUA Desktop/pedestal Rack

16x10Base-T

100Base-TX

1000Base-T

2xSFP PoE ports

16 CS4220-

16GT-240

Modelis: CS4220-16GT-240

Gamintojas: DAHUA

EAN: 6923172571205

Prekės kodas: 68157

189.99€

Highly intuitive, the Smart Managed Switch can manage local networks. With the DoLynk Care platform, it can also perform cloud management. The switch performs operation and maintenance using topology visualization on front-end, transmission and back-end storage devices that are in the security system and IT system. With its full metal design, the switch has great heat dissipation and

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

can operate in

temperatures ranging -10°C to 55°C. It offers EMC and has protection against overvoltage, overcurrent, static electricity, lightning strikes, pulses and other types of interference. For the PoE series Smart

Managed Switch, power is supplied up to 250 meters away. The orange port supplies up to 60 W and the red port provides up to 90 W. Also, link aggregation and STP are available on select models to ensure

the network remains stable. The switch can be used in small and medium-sized businesses such as supermarkets, offices, restaurants, cafés and hotels.

- Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x, IEEE802.3ab,IEEE802.3z standards
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE
- A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof

Summary: Dahua Technology CS4220-16GT-240. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 18. MAC address table: 8000 entries, Switching capacity: 40 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE.... Power over Ethernet (PoE). Rack mounting | Vendor Homepage:

<https://transmission.dahuasecurity.com/en/product->

[list/Business/CloudManagementSolution/NetworkSwitch/CS4220-16GT-240](https://transmission.dahuasecurity.com/en/product-list/Business/CloudManagementSolution/NetworkSwitch/CS4220-16GT-240) | Cloud-managed: Yes |

Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45

Ethernet ports quantity: 18 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet

(10/100/1000) | SFP module slots quantity: 2 | 10G support: No | Flow control support: Yes |

Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3ae/IEEE 802.3at/IEEE 802.3bt/IEEE

802.3u/IEEE 802.3x/IEEE 802.3z | Number of VLANs: 32 | Spanning tree protocol: Yes | VLAN support:

Yes | Forwarding rate: 29.76 | Jumbo frames: 15360 | Jumbo frames support: Yes | MAC address

table: 8000 | Switching capacity: 40 | DHCP features: DHCP client | Loop protection: Yes | Housing

material: Metal | Product colour: Black | Rack mounting: Yes | Reset button: Yes | AC input frequency:

47/63 | AC input voltage: 100 - 240 | Power consumption (typical): 265 | Power source: AC/DC/PoE |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 16 | Total Power over Ethernet (PoE) budget: 240 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 220 | Height: 44 | Weight: 2370 | Width: 440 | Package depth: 342 | Package height: 90 | Package weight: 3020 | Package width: 540 | Units per Pallet: 0 | Units per Shipping Box: 5 | Unit Calculated Volume: 0.01987 | Unit Calculated Weight: 3.6

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903