



# Switch DAHUA PoE ports 8 PFS3211-8GT- 120-V2



Modelis: PFS3211-8GT-120-V2

Gamintojas: DAHUA

EAN: 6923172525482

Prekės kodas: 68178

## 212.98€

DH-PFS3211-8GT-120 is an unmanaged Hardened PoE Switch with 8 × 10/100/1000 Mbps PoE Ports. It provides 8 × 10/100/1000 Mbps Ethernet ports , 2 × 1000 Mbps uplink SFPs and 1 ×10/100/1000 Mbps Ethernet uplink ports . The product is equipped with two types of transmission modes (Extend Mode On/Extend Mode Off). The red port supports the IEEE802.3bt and the Hi-PoE standards. The maximum power consumption is 120W. It also supports PoE watchdog to avoid manually maintenance and device restart, which can realize the intelligent management and reduce the cost.

### Intelligent PoE

Provides control over power consumption and offers real-time monitoring to ensure power supplies receive priority with important ports and to prevent malfunctions caused by changes in power consumption. Supports ultra wide power supplies and is able to adapt to IPC power fluctuations.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

## **BT 90W**

The red ports support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards, with a maximum output power consumption rate of 90W per port. Suitable for powering high-power devices.

## **PoE Watchdog**

Adopts the innovative PoE Watchdog. PoE Watchdog can be switched on by dialing or turning on the WEB page switch. It enables the switch to automatically detect port status and restart failed ports to recover connection in case of IPC connection exception. This enables intelligent operation and maintenance management in its truest sense, effectively reducing manual maintenance costs.

## **Long Distance PoE**

By dialing or enabling long-range transmission on the WEB interface, the transmission distance of a PoE port can be up to 250 m, meeting the requirements of wired transmission (bandwidth reduced to 10 Mbps).

## **8-pin Assignment PoE Power Supply**

Supports 8-pin simultaneous power supply (1/2/4/5 positive, 3/6/7/8 negative). Signal lines and idle lines supply power at the same time. Compatibility with IPC is enhanced. Cable loss is reduced. Loading capacity is increased.

The device is applicable for use in different scenarios, including home, office, server farm, and small mall.

- Intelligent PoE
- 8-pin assignment PoE power supply
- Long distance PoE
- PoE watchdog
- BT 90W
- All-giga ports
- Wide working temperature
- Anti-theft Lock Hole

Summary: Dahua Technology PFS3211-8GT-120-V2. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity:

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

9. Switching optical modules type: Gigabit Ethernet. Installed SFP modules quantity: 2. Switching capacity: 33 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u,.... DC input voltage: 48 - 57 V. Power over Ethernet (PoE). Wall mountable, Form factor: Desktop/Wall-Mounting | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Dedicated-Products/Project-Exclusive/Transmission/PFS3211-8GT-120%28only-for-project%29> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 9 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 9 | Installed SFP modules quantity: 2 | 10G support: No | Cable types supported: Cat5e/Cat6 | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x | Switching optical modules type: Gigabit Ethernet | Forwarding rate: 16.37 | Packet buffer memory: 1.75 | Switching capacity: 33 | Form factor: Desktop/Wall-Mounting | LED indicators: Yes | Product colour: Black | Rack mounting: No | Stackable: No | Wall mountable: Yes | DC input voltage: 48 - 57 | Power consumption (max): 120 | Power consumption note: Idling: 5 W | Power management: Yes | Power protection features: Overdischarge | Power source: DC | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Power over Ethernet (PoE) power per port: 90 | Total Power over Ethernet (PoE) budget: 120 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -30 - 65 | Depth: 100 | Height: 42 | Weight: 670 | Width: 150 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.005184 | Unit Calculated Weight: 1.48

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903