



NET ROUTER 1/2.5G 6PORT VPN/OMADA ER707-M2 TP- LINK



Modelis: ER707-M2

Gamintojas: TP-LINK

EAN: 4895252500738

Prekės kodas: 68224

125.99€

Dual 2.5 Gbps Ports, Engineered for Dense Environments

Delivering high-speed transmissions through dual 2.5 Gbps ports, ER707-M2 is designed for multi-person environments such as retail stores, hotels, and offices. Enjoy a blazing-fast network experience while working from home.

6x WAN Ports & 1 USB WAN for Mobile Broadband

Empowered with up to 6x WAN SFP and RJ45 ports, ER707-M2 supports various internet access.△ Multi-WAN Load Balancing distributes data streams based on the bandwidth proportion of every WAN port to increase the utilization rate of multi-line broadband.

Connect a 4G/3G modem to the USB 2.0 port for a LTE WAN backup.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

High-Security VPN

Pass-through traffic and a variety of VPN protocols, such as SSL, GRE, IPSec, PPTP, and L2TP, are available on ER707-M2, giving consumers versatile options. One-click auto IPSec VPN simplifies VPN configuration and facilitates network management and deployment.* The router also features a built-in hardware engine to boost VPN performance.

Internet Access Management Strategy

Standardize users' online behavior and easily specify the internet access rights and strategies of employees via IP/MAC/URL Filtering and Access Control List (ACL). Captive Portal authentication facilitates network resource control by capturing, authenticating, and classifying user access. Appropriate network resources can also be allocated for particular users or guests.

Omada SDN—The Smarter Cloud Solution for Business Networking

As the router that seamlessly integrates into the Omada Software Defined Networking (SDN) platform, ER707-M2 allows for remote and centralized management, anywhere, anytime. Standalone management via the Web UI or app is also available to maximize convenience.

Easy Management with the Omada App

Follow configuration instructions on the free Omada app to get set up in minutes. Omada lets you configure settings, monitor the network status and manage clients, all from the convenience of a smart phone or tablet.

- Two 2.5G Ports: 1× 2.5G WAN and 1× 2.5G WAN/LAN ports provide high-bandwidth aggregation connectivity
- Up to 6 WAN Ports: 2.5G RJ45, gigabit Fiber, and gigabit RJ45 WAN ports with load balance raise the utilization rate of multi-line broadband
- Highly Secure VPN: Enterprise-standard SSL/IPSec/GRE/PPTP/L2TP VPN & OpenVPN are ideal for use across multiple branches and for WFH
- Integrated into Omada SDN: Supports Zero-Touch Provisioning (ZTP),** Centralized Cloud Management, Intelligent Monitoring, and more
- Centralized Management: Cloud access and Omada app provide the utmost in management convenience

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Extensive Security Features: Protect your network and data with advanced firewall policies, DoS defense, IP/MAC/URL filtering, and more security functions

Summary: TP-Link Omada Multi-Gigabit VPN Router. Networking standards: IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3q, IEEE 802.3u, IEEE 802.3x, Ethernet interface type: 2.5 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000,2500 Mbit/s. Supported network protocols: TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, HTTPS, DNS, IPSec, PPTP, L2TP, OpenVPN, SNMP. Security algorithms: 3DES, 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SNMP, SNMPv2, SNMPv3. Compliance certificates: CE, Federal Communications Commission (FCC), RoHS. Flash memory: 128 MB, Internal memory: 1000 MB, Internal memory type: DDR4 | Vendor Homepage: <https://www.tp-link.com/uk/business-networking/omada-sdn-router/er707-m2/> | Ethernet WAN: Yes | SFP WAN: Yes | Ethernet interface type: 2.5 Gigabit Ethernet/Fast Ethernet/Gigabit Ethernet | Ethernet LAN data rates: 10/100/1000/2500 | Networking standards: IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3q/IEEE 802.3u/IEEE 802.3x | Policy-based routing: Yes | Static route: Yes | Throughput: 1.44 | VLAN support: Yes | Reset button: Yes | Universal Plug and Play (UPnP): Yes | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 6 | Installed SFP modules quantity: 1 | USB ports quantity: 1 | USB version: 2.0 | WAN ports quantity: 1 | WAN/Ethernet LAN ports quantity: 6 | DHCP client: Yes | DHCP server: Yes | DMZ support: Yes | Supported network protocols: TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, HTTPS, DNS, IPSec, PPTP, L2TP, OpenVPN, SNMP | Access Control List (ACL): Yes | ICMP attack prevention: Yes | Network address translation (NAT): Yes | Security algorithms: 128-bit AES/192-bit AES/256-bit AES/3DES/DES/MD5/SHA-1/SNMP/SNMPv2/SNMPv3 | System event log: Yes | URL filtering: Yes | VPN tunnels quantity: 66 | AC adapter included: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Quick installation guide: Yes | Sustainability compliance: Yes | Flash memory: 128 | Internal memory: 1000 | Internal memory type: DDR4 | Linux operating systems supported: Yes | Mac operating systems supported: Yes | Windows operating systems supported: Windows 10/Windows 2000/Windows 7/Windows 8/Windows 8.1/Windows 98SE/Windows NT/Windows Vista/Windows XP | Housing material: Steel | LED indicators: LAN/Link/Power/Speed/System/USB/WAN | Product colour: Black | Wall mountable: Yes | Output current: 1.5 | Output voltage: 12 | Power source type: DC | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 131 | Height: 35 | Width: 226 | Package depth: 323 | Package height: 73 | Package weight: 1100 | Package width: 242 | Model: ER707-M2 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.004469 | Unit Calculated Weight: 1.5

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903