



# Switch MIKROTIK CRS310-1G-5S- 4S+IN Type L3 PoE ports 1 CRS310-1G-5S- 4S+IN

Modelis: CRS310-1G-5S-4S+IN

Gamintojas: MIKROTIK

EAN: 4752224007827

Prekės kodas: 68234

---

## 170.99€

---

10 Gigabit fibre connectivity way over a 100 meters – for small offices or ISPs. Hardware offloaded VLAN-filtering and even some L3 routing on a budget!

This switch is an indoor variation of the prominent netFiber 9 switch – used by many small and medium ISPs for reliable 10 Gigabit fibre connections stretching over a 100 meters. With five 1G SFP ports, four 10G SFP+ ports, and an additional Gigabit Ethernet port, this is the perfect upgrade for existing CRS212 setups. You're getting the modern ARM v7 CPU, 256 MB of RAM, and better cooling. The new Marvell switch-chips bring phenomenal performance to the table!

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

The Gigabit Ethernet port has a direct connection to the switch chip – so you can enjoy full gigabit speed there. And it supports PoE-in, giving you an additional powering option in tricky spots.

You can mount this switch in a standard 1U rack to keep everything organized. And it has all the power you would expect from a rackmount device: CRS310 supports hardware offloaded VLAN-filtering. And even some hardware offloaded Layer-3 routing.

CRS310-1G-5S-4S+IN is a fantastic tool for anyone working with indoor connections over 100 meters while keeping data loss and ping low. Optical fiber can be a great alternative to copper if you are worried about electromagnetic interference, tampering or eavesdropping.

Summary: Mikrotik CRS310-1G-5S-4S+IN. Switch type: Managed, Switch layer: L3. Console port: RJ-45. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 18 - 57 V. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage:

[https://mikrotik.com/product/crs310\\_1g\\_5s\\_4s\\_in](https://mikrotik.com/product/crs310_1g_5s_4s_in) | Switch layer: L3 | Switch type: Managed | Console port: RJ-45 | SFP module slots quantity: 5 | SFP+ module slots quantity: 4 | 10G support: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Form factor: 1U | Rack mounting: Yes | Reset button: Yes | Built-in processor: Yes | Flash memory: 16 | Internal memory: 256 | Mean time between failures (MTBF): 200000 | Processor frequency: 800 | Processor model: 98DX226S | DC input voltage: 18 - 57 | Power consumption (max): 20 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Operating temperature (T-T): -40 - 70 | Depth: 166 | Height: 45 | Width: 200 | Certification: CE, EAC, ROHS | Harmonized System (HS) code: 85176990 | Model name: CRS310-1G-5S-4S+IN | Units per Shipping Box: 1 | Unit Calculated Volume: 0.00372 | Unit Calculated Weight: 1.04