



**Switch DAHUA
CS4010-8GT-110
Type L2
Desktop/pedestal
8x10Base-T
100Base-TX
1000Base-T PoE
ports 8 DH-
CS4010-8GT-110**

Modelis: DH-CS4010-8GT-110

Gamintojas: DAHUA

EAN: 6923172571151

Prekės kodas: 68257

89.00€

- Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab standards
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof

Summary: Dahua Technology DH-CS4010-8GT-110. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x. DC input voltage: 54 V. Power over Ethernet (PoE) | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/Cloud-Managed-Switches/CS4010-8GT-110> | Cloud-managed: Yes | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 10 | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 32 | Spanning tree protocol: Yes | Virtual LAN features: Port-based VLAN | VLAN support: Yes | Forwarding rate: 4.17 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 0.5 | Switching capacity: 20 | DHCP features: DHCP client | Housing material: Metal | LED indicators: Yes | Product colour: Black | Rack mounting: No | Reset button: Yes | DC input voltage: 54 | Input current: 2.22 | Power consumption (max): 110 | Power source: DC/PoE | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 106 | Height: 30 | Weight: 550 | Width: 190 | Package depth: 244 | Package height: 87 | Package weight: 1300 | Package width: 256 | Sustainability compliance: Yes | Compliance certificates: CE | Model name: CS4010-8GT-110 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.005623 | Unit Calculated Weight: 1.28

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903