



**Switch TP-LINK  
Omada TL-  
SG2008P Type  
L2+  
Desktop/pedestal  
8x10Base-T  
100Base-TX  
1000Base-T  
PoE+ ports 4 62  
Watts TL-  
SG2008P**

Modelis: TL-SG2008P

Gamintojas: TP-LINK

EAN: 6935364072957

Prekės kodas: 68276

---

**111.99€**

---

TP-Link's brand new Omada smart switches provide huge upgrade comparing with previous versions. The switches can be managed by Omada SDN Controller, which provides professional and reliable

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

one-step solutions. Integrated L2 and L2+ features such as 802.1Q VLAN, QoS, IGMP Snooping and static routing provide cost-effective networking solutions for small and medium-sized businesses without sacrificing enhanced usability and strong performance.

- 8× Gigabit ports (4× 802.3at/af-compliant PoE+ ports)
- 62 W total PoE budget with up to 30 W PoE output per port\*
- Centralized cloud management via the web or the Omada app†
- Standalone management via web, CLI, SNMP, and RMON
- Static Routing helps route internal traffic for higher efficiency
- VLAN, ACL, QoS, and IGMP Snooping
- Fanless design for silent operation
- Durable metal casing and desktop/wall mounting design

Summary: TP-Link Omada 8-Port Gigabit Smart Switch with 4-Port PoE+. Switch type: Managed, Switch layer: L2/L2+. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 8000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE.... Power over Ethernet (PoE). Rack mounting | Vendor Homepage: <https://www.tp-link.com/en/business-networking/omada-switch-poe/sg2008p/> | ARP inspection: Yes | MIB support: MIB II (RFC1213) Bridge MIB (RFC1493) P/Q-Bridge MIB (RFC2674) Radius Accounting Client MIB (RFC2620) Radius Authentication Client MIB (RFC2618) Remote Ping, Traceroute MIB (RFC2925) Support TP-Link private MIBs RMON MIB(RFC1757, rmon 1,2,3,9) | Quality of Service (QoS) support: Yes | Switch layer: L2/L2+ | Switch type: Managed | System event log: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1D/IEEE 802.1p/IEEE 802.1Q/IEEE 802.1s/IEEE 802.1w/IEEE 802.1x/IEEE 802.3ab/IEEE 802.3ad/IEEE 802.3af/IEEE 802.3at/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 4094 | Port mirroring: Yes | Rate limiting: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Forwarding rate: 11.9 | Jumbo frames: 9000 | Jumbo frames support: Yes | MAC address table: 8000 | Number of queues: 8 | Packet buffer memory: 4.1 | Switching capacity: 16 | Authentication: MAC-based authentication, Web-based authentication | Authentication type: RADIUS | DHCP features: DHCP client/DHCP relay/DHCP snooping/DHCPv6 server/DHCPv6 snooping | IGMP snooping: Yes | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Multicast support:

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Yes | IPv4 & IPv6 features: IPv6 ping/IPv6 Telnet/IPv6 tracer | Management protocols: SNMPv1/v2c/v3 | LED indicators: Yes | Product colour: Black | Rack mounting: Yes | Fanless: Yes | Power consumption (max): 77.3 | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet plus (PoE+) ports quantity: 4 | Heat dissipation: 263.6 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 126 | Height: 26 | Width: 209 | Manual: Yes | Package type: Box | Certification: CE, FCC, RoHS | Series: Omada | Model name: TL-SG2008P | Units per Shipping Box: 1 | Unit Calculated Volume: 0.005292 | Unit Calculated Weight: 1.28

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903