

InLine 57885D KVM switch Rack mounting Black

Gamintojas: **INLINE** · Modelis: **57885D** · EAN: **4043718344277** · Prekės kodas: **683183**



193,90 €

Kaina su PVM

Be PVM: **160,25 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Rack mounting Black
- ✓ Number of computers controlled: 2
- ✓ Video port type: HDMI
- ✓ 8K Ultra HD 7680 x 4320 pixels
- ✓ Housing material: Metal
- ✓ DC 12 W External power adapter



Aprašymas

Four PCs, one workspace:Control four computers with just one mouse, keyboard and HDMI display – ideal for IT professionals, server rooms or training systems.

8K HDMI 2.1 + HDR10+:Brilliant image quality with Dolby Vision, HDR10+ and 4K@144Hz – even with graphics-intensive applications.

USB 3.2 Gen.1 hub for peripherals:Connect a webcam, storage device or printer – with 5 Gb/s on all four PCs.

Flexible control:Switch via button, hotkey, IR remote control or RS-232 – individually controllable and automatable.

Maximum compatibility:Platform-independent (Windows, macOS, Linux), no drivers required.

The InLine KVM Switch 4-way with HDMI 2.1 allows four computers to be controlled centrally from a single workstation – with one HDMI monitor, one mouse and one keyboard. It is ideal for IT departments, technical workstations or demanding home workstations with multiple systems.

Thanks to HDMI 2.1, the switch supports resolutions up to 8K@60Hz and HDR formats such as Dolby Vision, HDR10+ and HLG. The four USB 3.2 Gen.1 ports allow peripheral devices such as printers, external drives or webcams to be shared across all connected computers at speeds of up to 5 Gb/s.

Switching between the four sources can be done as required via hotkey, front button, IR remote control or RS-232 control. The robust metal housing, ESD protection and extensive accessories ensure smooth and professional operation. The switch is operating system independent and requires no drivers.

HDMI inputs: 4 × HDMI (Type A, 19-pin)

HDMI output: 1 × HDMI (Type A, 19-pin)

USB ports: 4 × USB 3.2 Gen.1 (USB-A), 4 × USB host (USB-B)

RS-232: 3-pin terminal connection

IR EXT: 3.5 mm stereo jack (38 kHz)

Audio output: 3.5 mm stereo jack (PCM 2.0CH)

Video resolution: up to 8K@60 Hz, 4K@120 Hz/144 Hz, 1080p@240 Hz

Colour depth: 8, 10, 12 bits

Colour spaces: RGB 4:4:4, YCbCr 4:4:4 / 4:2:2 / 4:2:0

HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG

HDMI version: HDMI 2.1

HDCP compatibility: HDCP 2.3

Audio formats HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD

Latency: no video or audio delay

CEC support: yes

ESD protection: ±8 kV air / ±4 kV contact

Housing: Metal housing, colour black

Dimensions: 270 × 100 × 30 mm

Weight: 756 g

Operating ambient temperature: 0–40 °C

Storage ambient temperature: –20–60 °C

Humidity: 20–90% (non-condensing)

Recommended HDMI cable lengths

Up to 2 m: 8K / 4K@120 Hz

Up to 5 m: Ultra HDMI 2.1

Up to 10 m: 1080p with standard cable

External power supply (power adapter)

Type: External plug-in power adapter with lock

Input voltage: 100–240 V AC, 50/60 Hz

Output voltage: 12.0 V DC

Output current: max. 1.0 A

Output power: 12.0 W

Average efficiency during operation: 85.23%

Efficiency at low load (10%): 78.53%

Power consumption at zero load: 0.09 W

Contents of delivery

1 × InLine® KVM switch, 4-port, HDMI, 8K60Hz

1 × IR remote control

1 × IR receiver cable (1.5 m, 38 kHz)

4 × HDMI cable (1.5 m)

- 4 × USB 3.2 Gen.1 cables (1.8 m, USB-A to USB-B)
- 1 × 12 V/1 A power supply with lock
- 1 × 3-pin terminal connection plug
- 2 × mounting brackets
- 4 × screws (KM3×4)
- 1 × user manual in German/English

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Ports & interfaces	
Number of computers controlled	2
Video port type	HDMI
HDMI ports quantity	5
HDMI version	2.1
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	4
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	4
USB connector type	USB Type-A, USB Type-B
Serial port type	RS-232
Serial ports quantity	1
Audio connections	Yes
DC-in jack	Yes
Performance	
HD type	8K Ultra HD
Maximum resolution	7680 x 4320 pixels
Data transfer rate (max)	5 Gbit/s
High Dynamic Range (HDR) supported	Yes
HDCP	Yes
Maximum refresh rate	240 Hz
HDCP version	2.3
Audio decoding technologies	DTS-HD, Dolby TrueHD, DTS-HD Master Audio, DTS:X, Dolby Digital EX, Dolby Atmos, Dolby Digital, Dolby Digital Plus
Consumer Electronics Control (CEC) support	Yes
Design	
Rack mounting	Yes
Product colour	Black
Housing material	Metal

LED indicators	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output voltage	12 V
Output current	1 A
Power consumption (typical)	12 W
External power adapter	Yes
Sustainability	
Compliance certificates	TÜV mark
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Weight & dimensions	
Width	270 mm
Depth	100 mm
Height	30 mm
Weight	758 g
Packaging data	
Package volume	14600 cm ³
Package type	Box
Packaging content	
Cables included	HDMI, IR, USB Type-A to USB Type-B
Manual	Yes
AC adapter included	Yes
Rack mount kit	Yes
Remote control included	Yes
Other features	
Dimensions (WxDxH)	270 x 100 x 30 mm
Colour depth	12 bit

Logistics data

Country of origin

Taiwan