

InLine 57885F KVM switch Rack mounting Black

Gamintojas: **INLINE** · Modelis: **57885F** · EAN: **4043718344291** · Prekės kodas: **683184**



143,91 €

Kaina su PVM

Be PVM: **118,93 €**

[Sandėlyje](#)




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Rack mounting Black
- ✓ Number of computers controlled: 2
- ✓ Video port type: HDMI
- ✓ 4K Ultra HD 3840 x 2160 pixels
- ✓ Housing material: Metal
- ✓ DC 12 W External power adapter



Aprašymas

Efficient control of two PCs with dual monitor setup: Operate two computers simultaneously via two HDMI monitors and shared USB peripherals.

High image quality with 4K60Hz support: Enjoy crystal-clear images in up to 4K@60Hz with full colour depth and HDR functionality.

Flexible control options for professional applications: Switching via hotkey, front button, IR remote control or RS-232 – ideal for individual working environments.

Maximum compatibility thanks to platform-independent technology: Works without drivers with Windows, macOS and Linux – ideal for mixed IT infrastructures.

Reliable operation thanks to sturdy metal housing: Robust construction and ESD protection ensure safe and long-lasting use in professional environments.

The InLine® KVM Switch, 2-port, HDMI, 4K60Hz, Dual Monitor, has been developed for professional users who want to efficiently operate two computers via a shared set of peripherals. With two HDMI outputs per PC, you can operate two monitors simultaneously – ideal for multitasking and

parallel work.

The device supports high-resolution image signals up to 4K@60Hz in full colour depth (4:4:4) including HDR, Dolby Vision and other modern video formats. Switching is convenient via hotkey, IR remote control, front button or RS-232 interface – just as you need it.

The integrated USB interface allows simultaneous access to keyboard, mouse, storage media or other USB 3.2 Gen.1 devices. Thanks to its driverless plug-and-play functionality, the KVM switch is ready for immediate use – across platforms under Windows, macOS and Linux.

Thanks to its high-quality metal housing, ESD protection and well-designed accessories, the device is perfect for control rooms, technical workstations or professional multi-system environments.

HDMI inputs: 4 × HDMI (2 per PC, A/B)

HDMI outputs: 2 × HDMI (display A and B)

USB ports: 2 × USB host (USB-B), 4 × USB 3.2 Gen.1 (USB-A)

Audio output: 3.5 mm stereo jack (PCM 2.0CH)

RS-232: 3-pin terminal connection

IR EXT: 3.5 mm stereo jack (38 kHz)

Resolution: up to 4K@60Hz, 2K@144Hz

Colour depth: 8 / 10 / 12 bits

Colour spaces: RGB, YCbCr 4:4:4, 4:2:2, 4:2:0

HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG

HDMI version: HDMI 2.0

HDCP compatibility: HDCP 2.3

Audio formats HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD

Latency: no video or audio delay

CEC support: yes

ESD protection: ±8 kV air / ±4 kV contact

Housing: metal housing, black

Dimensions: 220 × 100 × 30 mm

Weight: 626 g

Operating temperature: 0–40 °C

Storage temperature: –20–60 °C

Humidity: 20–90% (non-condensing)

Recommended HDMI cable lengths:

up to 5 m: 4K@60Hz (Premium High Speed HDMI)

up to 10 m: 1080p (standard HDMI cable)

External power supply (power adapter):

Type: External plug-in power adapter with lock

Input voltage: 100–240 V AC, 50/60 Hz

Output voltage: 12.0 V DC

Output current: max. 1.0 A

Output power: 12.0 W

Average efficiency in operation: 85.23%

Efficiency at low load (10%): 78.53%

Power consumption at zero load: 0.09 W

Scope of delivery:

1 × InLine® KVM switch, 2-port, HDMI, 4K60Hz, dual monitor

- 1 × IR remote control
- 1 × IR receiver cable (1.5 m, 38 kHz)
- 2 × HDMI cables (1.5 m each)
- 2 × USB cables (USB 3.2 Gen.1, USB-A to USB-B, 1.8 m)
- 1 × 12 V/1 A power supply with lock
- 1 × 3-pin terminal connection plug
- 2 × mounting brackets
- 4 × screws (KM3×4)
- 1 × user manual in German/English

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Switches [+2183][-1086]
Ports & interfaces	
Number of computers controlled	2
Video port type	HDMI
HDMI ports quantity	6
HDMI version	2.1
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	4
USB connector type	USB Type-A, USB Type-B
Serial port type	RS-232
Serial ports quantity	1
Audio connections	Yes
DC-in jack	Yes
Performance	
HD type	4K Ultra HD
Maximum resolution	3840 x 2160 pixels
High Dynamic Range (HDR) supported	Yes
HDCP	Yes
Maximum refresh rate	144 Hz
HDCP version	2.3
Audio decoding technologies	DTS-HD, Dolby TrueHD, DTS-HD Master Audio, DTS:X, Dolby Digital EX, Dolby Atmos, Dolby Digital, Dolby Digital Plus
Consumer Electronics Control (CEC) support	Yes
Design	
Rack mounting	Yes

Product colour	Black
Housing material	Metal
LED indicators	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output voltage	12 V
Output current	1 A
Power consumption (typical)	12 W
External power adapter	Yes
Sustainability	
Compliance certificates	TÜV mark
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Weight & dimensions	
Width	100 mm
Depth	220 mm
Height	30 mm
Weight	618 g
Packaging data	
Package volume	14600 cm³
Package type	Box
Packaging content	
Cables included	HDMI, IR, USB Type-A to USB Type-B
Manual	Yes
AC adapter included	Yes
Rack mount kit	Yes
Remote control included	Yes
Other features	

Dimensions (WxDxH)	100 x 220 x 30 mm
--------------------	-------------------

Colour depth	12 bit
--------------	--------

Logistics data

Country of origin	Taiwan
-------------------	--------