

Salicru SPS 700 ONE BL

Gamintojas: **SALICRU** · Modelis: **662AG000004** · EAN: **8436584874973** · Prekės kodas: **683213**



172,90 €

Kaina su PVM

Be PVM: **142,89 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 0.7 kVA 360 W
- ✓ Waveform: Pseudo sine
- ✓ 2 AC outlet(s)
- ✓ Lead-Calcium (Pb-Ca)
- ✓ Tower Black



Aprašymas

SPS ONE: The best electrical protection for home and professional office

An uninterruptible power supply (UPS) in a mini tower format with Line-interactive topology, Salicru's SPS ONE series provides battery backup (with pseudo sine wave inverter output) and overload protection. During power failures, SPS ONE devices provide battery backup to enable computer systems to shut down properly and protect against data loss and electronics damage. Operation through automatic voltage regulation (AVR) to correct small voltage fluctuations without having to use the battery, thus extending its life. The AVR function is essential in areas where voltage fluctuations occur frequently.

It features a UPS/PC communication interface via USB with HID protocol, which allows parameter setting, UPS control and shutdown or hibernation of the computer through the USB port. Compatible with Windows, Linux and Mac operating systems. UPS management and monitoring software is also available for closing files/applications for Windows, Linux and Mac families.

Techninė specifikacija

Specifications	
Sandėlio grupė	Energy Supply > UPS [+731][-388]
Features	
UPS topology	Line-Interactive
Output power capacity	0.7 kVA
Output power	360 W
Waveform	Pseudo sine
Input operation voltage (min)	162 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Response time	6 ms
Noise level	40 dB
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Battery replacement, Low battery alarm, Overload alarm
Auto-restart	Yes
Power source type	AC
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	2 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Battery	
Battery technology	Lead-Calcium (Pb-Ca)
Battery life (max)	5 year(s)
Battery recharge time	6 h
Cold start	Yes
Design	
Form factor	Tower

Product colour	Black
----------------	-------

Control type	Buttons
--------------	---------

LED indicators	Yes
----------------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Certificates

Certification	EN IEC 62040-1 EN IEC 62040-2 EN IEC 62040-3 ISO 9001, ISO 14001, ISO 45001
---------------	---

Weight & dimensions

Width	101 mm
-------	--------

Depth	300 mm
-------	--------

Height	142 mm
--------	--------

Weight	4.5 kg
--------	--------