



Access Point MIKROTIK IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac RBCAPGI- 5ACD2ND



Modelis: RBCAPGI-5ACD2ND

Gamintojas: MIKROTIK

EAN: 4752224003416

Prekės kodas: 68338

76.99€

MIKROTIK cAP ac

The cAP ac is a very capable and powerful wireless access point that looks beautiful on both walls and ceilings. The concurrent dual band wireless radio supports dual chain 2 GHz 802.11b/g/n and 5 GHz in a/n/ac standards, and will provide coverage in 360 degrees around it.

Even though the radio supports repeater mode, the two Ethernet ports give you the ability to extend your network with cables, even if PoE power is required, since the cAP ac supports 802.3af/at PoE

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

input on the first port, and passive PoE output on the second port. Device supports IPsec hardware acceleration too.

- cAP ac (International) supports 2412-2484MHz and 5150MHz-5875MHz range (Specific frequency range can be limited by country regulations).

- cAP ac-US (USA) is factory locked for 2412-2462MHz, 5170-5250MHz and 5725-5835MHz frequencies. This lock can not be removed.

Vendor Homepage: mikrotik.com/product/cap_ac | IEEE 802.11ac: Yes | IEEE 802.11b: Yes | IEEE 802.11g: Yes | IEEE 802.11n: Yes | Model name: cAP ac // RBcAPGi-5acD2nD | Network Device Type: Wireless Access Point | Dimensions: 185x31mm | Units per Shipping Box: 1 | Unit Calculated Volume: 0.002787 | Product Net Weight: 0.2 | Unit Calculated Weight: 0.68