



Switch TP-LINK

Switch type

Unmanaged

24xRJ-45 ports

RJ-45 Ports Type

Gigabit Ethernet

(10/100/1000)

LS1024G

Modelis: LS1024G

Gamintojas: TP-LINK

EAN: 1210002602136

Prekės kodas: 68340

72.00€

The LS1024G Gigabit Ethernet Switch provides you with a high-performance, low-cost, easy-to-use, seamless and standard upgrade to improve old network to 1000Mbps network. All 24 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the LS1024G can save power consumption, making it an eco-friendly solution for your business network.

- Supports MAC address self-learning, Auto MDI/MDIX and Auto Negotiation

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Plug & play design
- QoS ensures smooth traffic for latency sensitive applications such as voice or video
- Innovative energy-efficient technology saves power consumption
- Fanless design reduces power consumption and ensures silent operation, ideal for noise-sensitive homes or businesses
- Durable metal casing provides improved heat dissipation and ensures a longer product life
- Desktop or rackmount installation

Summary: TP-Link LS1024G. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 8000 entries, Switching capacity: 48 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x | Vendor Homepage: <https://www.tp-link.com/au/business-networking/soho-switch-unmanaged/ls1024g/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3i/IEEE 802.3p/IEEE 802.3u/IEEE 802.3x | Forwarding rate: 35.712 | Jumbo frames: 10000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 2 | Store-and-forward: Yes | Switching capacity: 48 | Product colour: Black | Rack mounting: No | Fanless: Yes | Mean time between failures (MTBF): 1183684 | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Input current: 0.6 | Power consumption (max): 12.6 | Power source: AC | Power supply included: Yes | Heat dissipation: 42.77 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 45 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 140 | Height: 44 | Width: 294 | Cables included: Power | Rack mount kit: Yes | User guide: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Model: LS1024G | Units per Shipping Box: 1 | Unit Calculated Volume: 0.006392 | Unit Calculated Weight: 1.95