



Switch TP-LINK Desktop/pedestal 16x10Base-T 100Base-TX 1000Base-T TL- SG116E



Modelis: TL-SG116E

Gamintojas: TP-LINK

EAN: 6935364084301

Prekės kodas: 68341

72.00€

What This Product Does

The TL-SG116E Unmanaged Pro switch is an ideal upgrade on unmanaged switches, suited for home and small business networks. A plug-and-play design makes for easy deployment without the need for a technician, while a robust metal casing provides better protection for components. Equipped with intelligent management features like QoS, VLAN, IGMP Snooping and more, this switch is effective in both simple and more demanding network environments.

Easy to Use

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Connecting devices to TL-SG116E is simple. Auto MDI/MDI-X crossover on all ports eliminate the need for crossover cables or uplink ports. Auto-negotiation on each port detects the link speed of a network device and intelligently adjusts settings for compatibility and optimal performance.

Durable Metal Casing

The interior components of TL-SG116E are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, TL-SG116E delivers switching performance you can depend on. Its compact size makes it ideal for deployment on desktops or work benches.

Additional Software Features

TL-SG116E excels not only in simple plug-and-play networks but also in more demanding environments. Network monitoring enables users to observe traffic behavior. Port Mirroring, Loop Prevention and Cable Diagnostics allow connection problems on your network to be identified and located. Administrators can designate the priority of traffic based on Port/802.1p/DSCP QoS, for example, to ensure that voice and video applications remain clear and lag-free. Combining security with network performance, TL-SG116E supports MTU VLAN, port-based VLAN and 802.1Q-based VLAN functions.

Go Green with Your Ethernet

TP-Link's latest generation of Unmanaged Pro Switches make use of innovative energy-saving technologies. Power consumption automatically adjusts according to link status and cable length, allowing you to expand your network while minimizing your carbon footprint. Save the planet and lower your energy bills — it's a win-win!

- 16 10/100/1000Mbps RJ45 ports
- Plug and play, with no configuration required
- Durable metal casing of superior quality and professional appearance
- Intelligent management via a web user interface and downloadable utility
- Green technology reduces power consumption

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Summary: TP-Link 16-Port Gigabit Unmanaged Pro Switch. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Full duplex. MAC address table: 8000 entries, Switching capacity: 32 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u | Vendor Homepage: https://www.tp-link.com/us/products/details/cat-5711_TL-SG116E.html | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 16 | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Cable length detection: Yes | Cable types supported: Cat3/Cat4/Cat5/Cat5e/Cat6 | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Full duplex: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1p/IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3u | Number of VLANs: 32 | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Protocol-based VLAN/Tagged VLAN | VLAN support: Yes | Forwarding rate: 23.81 | Jumbo frames: 10000 | Jumbo frames support: Yes | MAC address table: 8000 | Number of queues: 4 | Packet buffer memory: 4.1 | Store-and-forward: Yes | Switching capacity: 32 | IGMP snooping: Yes | Loop protection: Yes | Housing material: Metal | LED indicators: Yes | Product colour: Black | Rack mounting: No | Plug and Play: Yes | Input current: 1 | Input voltage: 12 | Power consumption (max): 9.19 | Power source: DC | Power supply included: Yes | Power over Ethernet (PoE): No | Heat dissipation: 31.68 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 111.7 | Height: 25.4 | Width: 286 | Cables included: AC | Quick start guide: Yes | AC adapter included: Yes | Package depth: 412 | Package height: 70 | Package weight: 1360 | Package width: 170 | Rubber feet: Yes | Certification: FCC, CE, RoHS | Harmonized System (HS) code: 85176990 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.006046 | Unit Calculated Weight: 1.43

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903